

# PRODUCT DATASHEET SMART+ Wifi Flare Wall UpDown RGB + W

Smart+ Up Down Flare Multicolor | Luminaire with WIFI technology



#### Areas of application

- General illumination
- Gardens
- Patios, balconies

## Product benefits

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options

#### **Product features**

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFi
- Type of protection: IP44



## **TECHNICAL DATA**

## Electrical data

Nominal wattage	14.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	101.000 mA
Inrush current	4.16 A
Power factor $\lambda$	> 0.5
Total harmonic distortion	< 20 %
Protection class	1
Operating mode	Mains voltage

## Photometrical data

Luminous flux	1000 lm
Total luminous flux of contained light sources	1350 lm
Luminous efficacy	71 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	< 6 sdcm
Flickering metric (Pst LM)	≤1 %
Stroboscope effect metric (SVM)	≤0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	320 °

# Dimensions & Weight

Length	132.00 mm
Width	100.00 mm
Height	246.00 mm
Product weight	820.00 g

SMART OUTD WIFI UPDFLARE WALL RGBWDG

## Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
With light source	Yes

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	12500

## **Emergency lighting**

Int	egrated test switch	No

#### Certificates & Standards

Standards	CE / UKCA
Replaceable light source (EPREL)	Not replaceable

#### **EQUIPMENT / ACCESSORIES**

- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### DOWNLOAD DATA

Documents and certificates		Document name	
PDF	User instruction / safety instructions	SMART WIFI FLARE	
PDF	Declarations of conformity	EC_SMART OUTD WIFI	
PDF	EU Data Act	SMART WiFi Lamps and Luminaires	

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075564305	Folding box 1	142 mm x 107 mm x 252 mm	1032.00 g	3.83 dm <sup>3</sup>
4058075564312	Shipping box 4	300 mm x 230 mm x 280 mm	4526.00 g	19.32 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/en-int/home-lighting/services/faq

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.