

# PRODUCT DATASHEET SMART+ Wifi Planon 450x450mm TW

SMART+ Planon Frameless TW | Frameless panel luminaires with WiFi technology

#### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



## Product benefits

- Easy and quick installation

#### **Product features**

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Dimmable
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Network protocol: WiFi



#### TECHNICAL DATA

#### Electrical data

Nominal wattage	28.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	137.500 mA
Max. number of luminaires per miniature circuit breaker B16	16
Max. number of luminaires per miniature circuit breaker C16	24
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	П
Operating mode	Mains voltage

#### Photometrical data

Luminous flux	2300 lm	
Total luminous flux of contained light sources	3000 lm	
Luminous efficacy	82 lm/W	
Color temperature	30006500 K	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Flickering metric (Pst LM)	≤1	
Stroboscope effect metric (SVM)	≤0.4	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	110 °	

## **Dimensions & Weight**

Length	450.00 mm
Width	450.00 mm
Height	62.00 mm
Product weight	2770.00 g

SMART WIFI PLANON FRAMELESS 45X45TW

#### Materials & Colors

Product color	White	
Housing color	White	
Body material	Aluminum	
Cover material Polymethylmethacrylate (PMMA)		
Light emitting surface material	PMMA	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

## **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	15000

## Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

## Additional product data

## EQUIPMENT / ACCESSORIES

- Mounting bracket included

- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	SMART+ PLANON FRAMELESS
PDF	Declarations of conformity	SMART WIFI PLANON FRAMELESS 45X45TW
PDF	Declarations of conformity UKCA	SMART WIFI AND SUNATHOME
POF	EU Data Act	SMART WiFi Lamps and Luminaires

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075484375	Folding box 1	485 mm x 95 mm x 487 mm	3093.00 g	22.44 dm <sup>3</sup>
4058075484382	Shipping box 4	502 mm x 399 mm x 512 mm	1367.00 g	102.55 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **References / Links**

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.