

# PRODUCT DATASHEET SMART+ Wifi Orbis Cylinder Gray 450mm TW

Cylinder | Decorative ceiling luminaires with WiFi technology



#### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

# Product benefits

- Easy and quick installation

## **Product features**

- Controllable via voice control available: Google Assistant or Amazon Alexa
- $\,$  Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi
- $-\,$  Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0)



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	26.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	128.000 mA
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	1
Operating mode	Mains voltage


# Photometrical data

Luminous flux	1050 lm
Total luminous flux of contained light sources	2490 lm
Luminous efficacy	96 lm/W
Color temperature	30006500 K
Reference control setting of contained light source (Kelvin)	3000 K <sup>1)</sup>
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	120 °

<sup>1)</sup> Performing a reset will restore the default values set by the manufacturer

# Dimensions & Weight

Diameter	450.00 mm
Height	134.00 mm
Product weight	2820.00 g



## Materials & Colors

Product color	Gray	
Housing color	Gray	
Body material	Polymethylmethacrylate (PMMA)	
Cover material	Polymethylmethacrylate (PMMA)	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

# Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Screw terminal
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
With light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

# Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

Replaceable light source (EPREL)	Not replaceable
Additional product data	

## **EQUIPMENT / ACCESSORIES**

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name	
User instruction / safety instructions SN		SMART ORBIS CYLINDER	
POF	Legal information	Legal insert SUNATHOME WORKSPACE	
POF	Declarations of conformity	SMART WIFI ORBIS CYLNR RD 450 TW GRLEDV	
POF	EU Data Act	SMART WiFi Lamps and Luminaires	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075486584	Folding box	502 mm x 148 mm x 504 mm	3272.00 g	37.45 dm <sup>3</sup>
4058075516632	Shipping box	525 mm x 463 mm x 528 mm	10837.00 g	128.34 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

TW

## References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.