

PRODUCT DATASHEET SST PLUS SPOT PAR16 80 120° 6.7 W/4000 K 220...240 V GU10

LED REFLECTOR PAR16 S | Dimmable LED reflector lamps PAR16 with bajonett base, natural daylight



Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to a halogen lamp
- Natural light spectrum with outstanding color rendering of CRI > 90
- Greatly reduced blue component
- Improved visual comfort and reduced eye strain
- Low maintenance costs and cost savings thanks to long lifetime
- Low flickering
- Lower energy consumption than incandescent or halogen lamps

Product features





- LED alternative to conventional low voltage lamps
- Dimmable
- Base: GU10
- Color rendering index R_a : ≥ 90
- Lamp made of glass

TECHNICAL DATA

Electrical data

Nominal wattage	6.7 W
Construction wattage	6.70 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	46 W
Nominal current	36 mA
Type of current	AC
Inrush current	0.249 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	222
Max. lamp number on MCB B16 A	350
Total harmonic distortion	≤ 150 %
Power factor λ	≥ 0.70

Photometrical data

Luminous intensity	200 cd
Luminous flux	575 lm
Nominal useful luminous flux 90°	575 lm
Luminous efficacy	85 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥90
Light color	940
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	200 cd
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



Everlight 67-23ST HKE 4000K

Light technical data

Beam angle	120 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	55.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	40.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	95 °C

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes
Certificates & Standards	

Energy efficiency class	F 1)
Energy consumption	7.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	LCPAR16801206,7	
Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	LED	
Non-directional or directional	NDLS	
Mains or non-mains	MLS	
Light source cap-type (or other electric interface)	GU10	
Connected light source (CLS)	No	
Color-tuneable light source	No	
Envelope	No	
High luminance light source	No	
Anti-glare shield	No	
Correlated colour temperature type	SINGLE_VALUE	
Standby power	0 W	
Networked standby power for CLS	0 W	
Claim of equivalent power	Yes	
Length	55.00 mm	
Height	50.00 mm	
Width	50.00 mm	
Chromaticity coordinate x	0.382	
Chromaticity coordinate y	0.380	
R9 Colour rendering index	1	
Beam angle correspondence	SPHERE_360	
Survival factor	0.90	
Displacement factor	0.50	

LED light source replaces a fluorescent light source	No
EPREL ID	642825
Model number	AC35790

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	PAR11 PAR16 GU10
	Photometric and lighting design files	Document name
	Spectral power distribution	Everlight 67-23ST HKE 4000K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075757929	Folding box 1	49 mm x 49 mm x 62 mm	47.00 g	0.15 dm ³
4058075757936	Shipping box 10	255 mm x 107 mm x 72 mm	523.00 g	1.96 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.