

# PRODUCT DATASHEET LED EDISON 60 DIM S 60 5.8 W/4000 K E27

LED CLASSIC EDISON | Dimmable LED lamps, classic Edison bulb shape



#### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lamps with innovative LED "filament" technology
- Natural light spectrum with outstanding color rendering of CRI > 90
- Greatly reduced blue component
- Improved visual comfort and reduced eye strain
- Lower energy consumption than incandescent or halogen lamps
- Instant 100 % light, no warm-up time
- Low flickering

#### **Product features**

- LED lamps for line voltage
- Beam angle: up to  $300^{\circ}$
- Dimmable





– Color rendering index  $R_a$ :  $\geq 90$ 

## TECHNICAL DATA

## Electrical data

| Nominal wattage                        | 5.8 W    |  |
|--|----------|--|
| Construction wattage                   | 5.80 W   |  |
| Nominal voltage                        | 220240 V |  |
| Operating mode                         | AC Mains |  |
| Claimed equiv. conventional lamp power | 60 W     |  |
| Nominal current                        | 36 mA    |  |
| Type of current                        | AC       |  |
| Inrush current                         | 0.46 A   |  |
| Operating frequency                    | 50/60 Hz |  |
| Mains frequency                        | 50/60 Hz |  |
| Max. lamp number on MCB B10 A          | 1406     |  |
| Max. lamp number on MCB B16 A          | 2250     |  |
| Power factor $\lambda$                 | > 0.50   |  |

### Photometrical data

| Luminous flux                           | 806 lm     |
|---|------------|
| Nominal useful luminous flux 90°        | 806 lm     |
| Luminous efficacy                       | 138 lm/W   |
| Lumen main.fact.at end of nom.life time | 0.93       |
| Light color (designation)               | Cool White |
| Color temperature                       | 4000 K     |
| Color rendering index Ra                | ≥90        |
| Light color                             | 940        |
| Standard deviation of color matching    | ≤6 sdcm    |
| Rated LLMF at 6,000 h                   | 0.80       |
| Flickering metric (Pst LM)              | ≤1         |
| Stroboscope effect metric (SVM)         | ≤ 0.9      |
| -                                       | ·          |



LISO spectral power distribution 4000K CRI80 v1

## Light technical data

| Beam angle          | 300 °    |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

## Dimensions & Weight

| Overall length   | 143.00 mm |
|------------------|-----------|
| Diameter         | 64.00 mm  |
| Maximum diameter | 64 mm     |
| Product weight   | 46.00 g   |

## Temperatures & operating conditions

| Ambient temperature range            | -20+40 °C |
|--------------------------------------|-----------|
| Maximum temperature at tc test point | ≤65 °C    |

## Lifespan

| Lifespan L70/B50 at 25 °C                    | 15000 h |
|--|---------|
| Number of switching cycles                   | 100000  |
| Lumen maintenance at end of service lifetime | 0.93    |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90  |

# Additional product data

| Base (standard designation) | E27    |
|-----------------------------|--------|
| Mercury content             | 0.0 mg |
| Mercury-free                | Yes    |
| Design / version            | Clear  |

| Product remark  | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |
|---|--|
| Capabilities  |  |
| Dimmable  | Yes  |
| Certificates & Standards  |  |
| Energy efficiency class   | D 1)   |
| Energy consumption  | 6.00 kWh/1000h   |
| Type of protection  | IP20   |
| Standards   | CE   |
| Photobiological safety group acc. to EN62778  | RG0  |
| Order reference   | LEDCEDIS60 5,8W  |
|   |  |
| OCIETICAL DATA  |  |
|   | 40 0000  |
| LOGISTICAL DATA  Temperature range at storage   | -40+80 °C  |
| Temperature range at storage  | -40+80 °C  |
| Temperature range at storage  | -40+80 °C  |
| Temperature range at storage  Energy labelling regulation data acc EU 2019/2015   |  |
| Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used   | LED  |
| Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional   | LED NDLS   |
| Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains   | LED NDLS MLS   |
| Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  | LED NDLS MLS E27   |
| Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  | LED  NDLS  MLS  E27  No  |
| Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source                             | LED NDLS MLS E27 No  |
| Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope   | LED  NDLS  MLS  E27  No  No  |
| Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source                    | LED  NDLS  MLS  E27  No  No  No  |
| Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield | LED NDLS MLS E27 No No No No No  |

143.00 mm

64.00 mm

Length

Height

E27

| Width  | 64.00 mm   |
|--|------------|
| Chromaticity coordinate x                            | 0,380      |
| Chromaticity coordinate y                            | 0.380      |
| R9 Colour rendering index                            | 1          |
| Beam angle correspondence                            | SPHERE_360 |
| Survival factor                                      | 0.90       |
| Displacement factor                                  | ≥0.5       |
| LED light source replaces a fluorescent light source | No         |
| EPREL ID   | 642806     |
| Model number   | AC34018    |

### **DOWNLOAD DATA**

|     | Documents and certificates | Document name |
|-----|----------------------------|---------------|
| PDF | Declarations of conformity | LED lamps DIM |

| Photometric and lighting design files | Document name                                   |
|---------------------------------------|---|
| Spectral power distribution           | LISO spectral power distribution 4000K CRI80 v1 |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075758124 | Folding box<br>1             | 65 mm x 65 mm x 147 mm               | 64.00 g      | 0.62 dm <sup>3</sup> |
| 4058075758131 | Shipping box<br>10           | 337 mm x 141 mm x 161 mm             | 749.00 g     | 7.65 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.