

# PRODUCT DATASHEET LED PAR16 UE 50 36 ° 2.2 W/2700 K GU10

LED LAMPS ENERGY EFFICIENCY REFLECTOR | LED reflector lamps PAR16, ENERGY EFFICIENCY CLASS B



#### Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

## Product benefits

- Design, dimensions, luminous flux comparable to a halogen lamp
- Low energy consumption
- Instant 100 % light, no warm-up time
- Low flickering

## Product features

- LED alternative to high voltage halogen lamps
- Very long lifetime of up to 50,000 h
- Luminous efficacy: up to 180 lm/W
- Very high number of switching cycles up to 100,000






# TECHNICAL DATA

# Electrical data

Nominal wattage	2.2 W
Construction wattage	2.20 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	50 W
Nominal current	22 mA
Type of current	AC
Inrush current	0.022 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	28
Max. lamp number on MCB B16 A	36
Total harmonic distortion	< 180 %
Power factor $\lambda$	≥ 0.40

## Photometrical data

Luminous intensity	850 cd
Luminous flux	350 lm
Nominal useful luminous flux 90°	350 lm
Luminous efficacy	159 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	850 cd
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0,4



LVK\_Spectrum\_AC33689

# Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	55.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	45.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	60 °C

# Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.96
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg

# Capabilities

Capabilities			
Dimmable	No		
Certificates & Standards			
Energy efficiency class	В		
Energy consumption	3.00 kWh/1000h		
Type of protection	IP20		
Standards	CE / EAC		
Photobiological safety group acc. to EN62778	RG1		
Country-specific categorizations			
Order reference	LED PAR165036 E		
LOGISTICAL DATA			
Temperature range at storage	-20+80 °C		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	LED		
Non-directional or directional	DLS		
Mains or non-mains	MLS		
Light source cap-type (or other electric interface)	GU10		
Connected light source (CLS)	No		
Color-tuneable light source	No		
Envelope	No		
High luminance light source	No		
Anti-glare shield	No		
Correlated colour temperature type	SINGLE_VALUE		
Standby power	not applicable		
Networked standby power for CLS	not applicable		
Claim of equivalent power	Yes		
Length	55.00 mm		
Height	50.00 mm		
Width	50.00 mm		
Chromaticity coordinate x	0.458		
Chromaticity coordinate y	0.410		
R9 Colour rendering index	1		
Beam angle correspondence	NARROW_CONE_90		

Survival factor	0,90
LED light source replaces a fluorescent light source	No
EPREL ID	1260025
Model number	AC43689

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### DOWNLOAD DATA

	Documents and certificates	Document name
POF	Declarations of conformity	LED lamp SPOT PAR16 50

Photometric and lighting design files Document na		Document name
	Spectral power distribution	LVK_Spectrum_AC33689

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854002960	Folding box	49 mm x 49 mm x 95 mm	55.00 g	0.23 dm <sup>3</sup>
4099854002977	Shipping box	168 mm x 111 mm x 71 mm	405.00 g	1.32 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee
- Further information see www.ledvance.com/low-voltage-ledlamps

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.