

# PRODUCT DATASHEET SMART+ BT Classic 60 9 W/2700 K E27

SMART+ Classic Dimmable | Classic bulb shape with Bluetooth technology



### Areas of application

- General illumination
- Outdoor use in suitable outdoor luminaires only

# Product benefits

- Easy to install and use
- Up to 80 % less energy consumption compared to halogen lamps
- Contains no mercury

### Product features

- LED Classic A lamp with wireless smart lighting function
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- For full functionality with control via Apple Home App connection to Apple TV (with tvOS 10 or later) or iPad (with iOS 10 or later) required
- Dimmable
- Network protocol: Bluetooth
- Lifetime: up to 20,000 h
- Your Smart Home obeys your word use Google Assistant and control your light via voice control






### **TECHNICAL DATA**

### Electrical data

Nominal wattage	9 W
Construction wattage	8.50 W
Nominal voltage	220240 V
Nominal current	55 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.5
Claimed equiv. conventional lamp power	60 W
Operating mode	AC Mains

### Photometrical data

Light color (designation)	Warm White
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	806 lm
Luminous flux	806 lm
Luminous efficacy	89 lm/W
Adjustable color temperature	2700 K
Color temperature	2700 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9



Everlight 67-23ST KKE 2700K

# Light technical data

|--|

Starting time	< 0.5 s
Light control	Adjustable color temperature
Warm-up time (60 %)	< 0.50 s
imensions & Weight	
Product weight	46.00 g
Diameter	60,0 mm
Maximum diameter	60 mm
Length	118.00 mm
Width	60,0 mm
Height	60,0 mm
Outer bulb [PICOS]	A60
fespan	
Number of switching cycles	100000
Lifespan	15000 h
Lumen maintenance at end of service lifetime	0.70
olors & materials	
Product color	White
Housing color	White
emperatures & operating conditions	
Ambient temperature range	-20+40 °C
dditional product data	
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the comple production process for light-emitting diodes, the typical values show for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E27

Yes 1)

Google Assistant / Amazon Alexa

Compatible smart home technology

Dimmable

<sup>1)</sup> Check dimmer compatibility at ledvance.com/compatibility

### Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	9.00 kWh/1000h
Standards	CE
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.50
Networked standby power for CLS	0.50
Claim of equivalent power	Yes
Chromaticity coordinate x	0.458
Chromaticity coordinate y	0.410
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360
Survival factor	0,9
Displacement factor	0.80
LED light source replaces a fluorescent light source	No
EPREL ID	1403083,528215
Model number	AC33928,AC25700

### **EQUIPMENT / ACCESSORIES**

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- For control via Apple Home App iPhone (with iOS 10 or later), iPad (with iOS 10 or later), Apple TV (with tvOS 10 or later) or Apple Watch (with watchOS 2 or later) required

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

### **DOWNLOAD DATA**

	Documents and certificates	Document name	
POF	User instruction / safety instructions	WWW UI SMART Homekit CLA60 E27 DIM	
POF	Extended installation guide	SMART+ INSTALLATION GUIDE	
POF	Declarations of conformity	SMART BT A60 DIM LEDVANCE	
POF	Declarations of conformity	EC Declaration of Conformity SMART+ BT CLA CLB CLP HS	
POF	Declarations of conformity	EC Declaration of Conformity SMART+ BT CLA60 AC25696 AC25698 AC25700 AC26958	
POF	EU Data Act	SMART Bluetooth Mesh Lighting Products	
	Photometric and lighting design file	es Document name	
	Spectral power distribution	Everlight 67-23ST KKE 2700K	

### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075208506	Folding box 1	61 mm x 96 mm x 154 mm	120.00 g	0.90 dm <sup>3</sup>
4058075211506	Shipping box 4	210 mm x 165 mm x 135 mm	613.00 g	4.68 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.