

# PRODUCT DATASHEET SMART+ BT Candle 40 4.9 W/2700...6500 K E14

SMART+ Candle Tunable White | Classic candle shape with Bluetooth technology



#### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Elegant aluminum reflector with optimized faceting
- Easy to install and use
- Contains no mercury

#### Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android™ 8.0 or iOS 14.0)
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Dimmable
- Network protocol: Bluetooth
- Lifetime: up to 20,000 h
- For full functionality with control via Apple Home App connection to Apple TV (with tvOS 10 or later) or iPad (with iOS 10 or later) required
- Your Smart Home obeys your word use Google Assistant and control your light via voice control






## TECHNICAL DATA

#### Electrical data

Nominal wattage	4.9 W
Construction wattage	4.90 W
Nominal voltage	220240 V
Nominal current	45 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Claimed equiv. conventional lamp power	40 W
Operating mode	AC Mains

## Photometrical data

Light color (designation)	Tunable White
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	470 lm
Luminous flux	470 lm
Luminous efficacy	95 lm/W
Adjustable color temperature	27006500 K
Color temperature	27006500 K
Color rendering index Ra	> 80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9




Everlight 67-23ST KKE 2700K

# Light technical data

Beam angle	220 °
Starting time	< 0.5 s

Light control	Adjustable color temperature
Warm-up time (60 %)	< 0.50 s

# Dimensions & Weight



Product weight	32.00 g
Diameter	39.00 mm
Maximum diameter	39 mm
Length	107.00 mm
Width	39.00 mm
Height	39.00 mm
Outer bulb [PICOS]	B40

## Lifespan

Number of switching cycles	100000
Lifespan	15000 h
Lumen maintenance at end of service lifetime	0.70

## Colors & materials

Product color	White
Housing color	White

# Temperatures & operating conditions

Ambient temperature range -20+40 °C
-------------------------------------

## Additional product data

Mercury-free	Yes

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E14

# Capabilities

Dimmable	Yes 1)
Compatible smart home technology	Google Home / Amazon Alexa

<sup>1)</sup> Check dimmer compatibility at ledvance.com/compatibility

## Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	5.00 kWh/1000h
Standards	CE
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	Yes
Color-tuneable light source	Yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	0.50
Networked standby power for CLS	0.50
Claim of equivalent power	Yes
Chromaticity coordinate x	0.458
Chromaticity coordinate y	0.410
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360

Survival factor	0.90
Displacement factor	0.50
LED light source replaces a fluorescent light source	No
EPREL ID	1403086,528219
Model number	AC33932,AC25703

#### **EQUIPMENT / ACCESSORIES**

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Extended installation guide	SMART+ INSTALLATION GUIDE	
PDF	Declarations of conformity	SMART BT B40/P40	
PDF	EU Data Act	SMART Bluetooth Mesh Lighting Products	
	Photometric and lighting design files	Document name	
<b>a</b>	Spectral power distribution	Everlight 67-23ST KKE 2700K	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485235	Folding box 1	61 mm x 96 mm x 154 mm	106.00 g	0.90 dm <sup>3</sup>
4058075485242	Shipping box 4	210 mm x 165 mm x 135 mm	534.00 g	4.68 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/en-int/home-lighting/services/faq

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.