

PRODUCT DATASHEET SMART+ Wifi Flare Post 60cm RGB + W

Smart+ Flare Multicolor | Luminaires with WiFi technology



Areas of application

- General illumination
- Gardens
- Patios, balconies

Product benefits

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFi
- Type of protection: IP44



TECHNICAL DATA

Electrical data


Nominal wattage	7.50 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Power factor λ	> 0.5	
Total harmonic distortion	< 20 %	
Protection class	1	
Operating mode	Mains voltage	

Photometrical data

Luminous flux	320 lm	
Total luminous flux of contained light sources	570 lm	
Luminous efficacy	43 lm/W	
Color temperature	3000 K	
Light color (designation)	RGBW	
Color rendering index Ra	≥80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	230.00 °	

Dimensions & Weight

Diameter	110.00 mm
Height	604.00 mm
Product weight	1150.00 g



Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20+40 °C	
Type of connection	Terminal, 3-Pole (L, N, PE)	
Type of protection	IP44	
Protection class IK (shock resistance)	IK03	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Wall	
Application environment	Outdoor	
With light source	No	

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	12500

Certificates & Standards

Standards	CE / EAC / UKCA

Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	SMART OUTD WIFI FLARE	
PDF	Legal information	Legal insert	
POF	Declarations of conformity	CE_SMART OUTD WIFI FLARE WALL RGBW DG	
PDF	Declarations of conformity UKCA	SMART WIFI	
PDF	EU Data Act	SMART WiFi Lamps and Luminaires	
-			

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075478299	Folding box 1	122 mm x 122 mm x 624 mm	1180.00 g	9.29 dm ³
4058075478305	Shipping box	638 mm x 258 mm x 147 mm	2892.00 g	24.20 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.