

# PRODUCT DATASHEET P LINE R7s 78.00 mm 100 12 W/2700 K R7s

PARATHOM® LINE R7s | Double-ended special LED lamps



#### Areas of application

- General illumination within ambient temperatures from -20...+40 °C
- Hospitality
- Domestic applications
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Fits into most R7s luminaires thanks to excentric base
- Good all-around light emission
- Long lifetime of up to 15,000 h
- Lower thermal output (compared with the standard reference product)
- Four year guarantee

#### **Product features**

- LED alternative to conventional R7s lamps






## TECHNICAL DATA

## Electrical data

Nominal wattage	12 W
Construction wattage	12.00 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	100 W
Nominal current	80 mA
Type of current	AC
Inrush current	5 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	43
Max. lamp number on MCB B16 A	51
Total harmonic distortion	< 180 %
Power factor $\lambda$	≥ 0.50

## Photometrical data

Luminous flux	1521 lm
Nominal useful luminous flux 90°	1521 lm
Luminous efficacy	126 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



349927\_2700K\_Evl\_5630.eps

# Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	78.00 mm
Diameter	28.00 mm
Maximum diameter	28 mm
Product weight	52.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at to test point	91 °C

# Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg
Design / version	Clear

## Capabilities

#### Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	12.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG1

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Country-specific categorizations

Order reference	LEDPLI78 100 12

## LOGISTICAL DATA

Temperature range at storage	-20+80 °C
------------------------------	-----------

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.00
Claim of equivalent power	Yes
Length	78.00 mm
Height	28.00 mm
Width	28.00 mm

Chromaticity coordinate y  R9 Colour rendering index  1  Beam angle correspondence  SPHERE_360  Survival factor  0.90  Displacement factor  0.70  LED light source replaces a fluorescent light source  EPREL ID  522894  Model number  AC32127	Chromaticity coordinate x	0.458
Beam angle correspondence  SPHERE_360  Survival factor  0.90  Displacement factor  0.70  LED light source replaces a fluorescent light source  No  EPREL ID  522894	Chromaticity coordinate y	0.410
Survival factor 0.90  Displacement factor 0.70  LED light source replaces a fluorescent light source No  EPREL ID 522894	R9 Colour rendering index	1
Displacement factor 0.70  LED light source replaces a fluorescent light source No  EPREL ID 522894	Beam angle correspondence	SPHERE_360
LED light source replaces a fluorescent light source  No  EPREL ID  522894	Survival factor	0.90
EPREL ID 522894	Displacement factor	0.70
	LED light source replaces a fluorescent light source	No
Model number AC32127	EPREL ID	522894
	Model number	AC32127

## Safety advice

- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	Declarations of conformity	LED SLIM LINE 78 60 NON-DIM	
	Photometric and lighting design files	Document name	
<u>~</u>	Spectral power distribution	349927_2700K_Evl_5630.eps	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075627055	Folding box 1	30 mm x 30 mm x 82 mm	55.00 g	0.07 dm <sup>3</sup>
4058075627062	Shipping box 20	159 mm x 129 mm x 91 mm	1145.00 g	1.87 dm <sup>3</sup>
4058075627079	Shipping box 120	269 mm x 169 mm x 291 mm	7025.00 g	13.23 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps

- For Guarantee see www.ledvance.com/guarantee

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.