

PRODUCT DATASHEET LED Value Classic B 60 6.8W 827 Frosted E14

LED VALUE CLASSIC B | LED lamps, classic mini-candle shape



Areas of application

- General illumination
- Domestic applications
- Chandeliers
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Simple direct replacement for conventional incandescent lamps
- Instant 100 % light, no warm-up time

Product features

- LED alternative to conventional lamps
- Not dimmable
- Good color rendering CRI \geq 80 and color stability throughout the life of the lamp






TECHNICAL DATA

Electrical data

onstruction wattage 6.80 W ominal voltage 220240 V perating mode AC Mains aimed equiv. conventional lamp power 60 W ominal current 55 mA rpe of current AC rush current 9.6 A perating frequency 50/60 Hz ax. lamp number on MCB B10 A	
perating mode AC Mains aimed equiv. conventional lamp power 60 W cominal current 55 mA AC rush current 9.6 A perating frequency 50/60 Hz ains frequency 50/60 Hz	
aimed equiv. conventional lamp power 60 W 55 mA pe of current AC rush current 9.6 A perating frequency 50/60 Hz 20/60 Hz	
per of current AC rush current 9.6 A perating frequency 50/60 Hz ains frequency 50/60 Hz	
pe of current 9.6 A perating frequency 50/60 Hz 50/60 Hz	
rush current 9.6 A perating frequency 50/60 Hz ains frequency 50/60 Hz	
perating frequency 50/60 Hz sains frequency 50/60 Hz	
ains frequency 50/60 Hz	
ax, lamp number on MCB B10 A	
ax. lamp number on MCB B16 A 69	
otal harmonic distortion 117.6 %	
ower factor λ 0.63	

Photometrical data

Luminous flux	806 lm
Luminous efficacy	118 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



Spectral graph Classic A 2700K DIM

E14

Light technical data

Beam angle	220 °
Warm-up time (60 %)	0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	103.00 mm
Diameter	35.00 mm
Maximum diameter	35 mm
Product weight	16.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	95 °C

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable

Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	7.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Temperature range at storage

Order reference	VALUECLB60 6,8W
LOGISTICAL DATA	

-20...+80 °C

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.0 W
Claim of equivalent power	Yes
Length	103.00 mm
Height	35.00 mm
Width	35.00 mm
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90

E14

Displacement factor	0.971
LED light source replaces a fluorescent light source	No
EPREL ID	1403235,523320,1381384,1351518,1838235,2192470,2187364
Model number	AC31162,AC44933,AC24722,AC45016,AC56451,AC56451,AC70653,AC70653,AC69358

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	Classic A_B_P 15000h FR	
PDF	Declarations of conformity	LED CLASSIC	
PDF	Declarations of conformity	CE declaration lamps	
PDF	Declarations of conformity UKCA	LED CLASSIC	
PDF	Declarations of conformity UKCA	UKCA Declaration lamps	
		5	
	Photometric and lighting design files	Document name	
	Spectral power distribution	Spectral graph Classic A 2700K DIM	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075152915	Folding box 1	38 mm x 38 mm x 108 mm	24.00 g	0.16 dm ³
4058075152922	Shipping box 10	198 mm x 84 mm x 119 mm	301.00 g	1.98 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

E14

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Page 6 of 6