

PRODUCT DATASHEET LED Value PAR16 80 36° 6.9W 865 GU10

LED VALUE PAR16 | LED reflector lamps PAR16 with retrofit pin base



Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Lower energy consumption than incandescent or halogen lamps

Product features

- LED alternative to high voltage halogen lamps
- Not dimmable
- Base: GU10
- Lamp made of glass
- Good quality of light; color rendering index CRI ≥ 80





TECHNICAL DATA

Electrical data

Nominal wattage	6.9 W
Construction wattage	6.90 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	80 W
Nominal current	50 mA
Type of current	AC
Inrush current	4.84 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	116
Max. lamp number on MCB B16 A	184
Total harmonic distortion	150 %
Power factor λ	> 0.50

Photometrical data

Luminous intensity	910 cd	
Luminous flux	575 lm	
Nominal useful luminous flux 90°	575 lm	
Luminous efficacy	83 lm/W	
Lumen main.fact.at end of nom.life time	0.93	
Light color (designation)	Cool Daylight	
Color temperature	6500 K	
Color rendering index Ra	80	
Light color	865	
Standard deviation of color matching	≤6 sdcm	
Rated peak intensity	910 cd	
Flickering metric (Pst LM)	1.0	
Stroboscope effect metric (SVM)	0.4	



OS 8W6551FL11L3 6500K

Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	54.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	39.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	97.5 °C

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg
Mercury-free	Yes

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	F 1)
Energy consumption	7.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG1
Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lower country-specific categorizations Order reference	
Country-specific categorizations	
	LVPAR168036 6,9
Country-specific categorizations	
Country-specific categorizations Order reference	
Country-specific categorizations Order reference OGISTICAL DATA	LVPAR168036 6,9
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage	LVPAR168036 6,9
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015	LVPAR168036 6,9 -20+80 °C
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used	LVPAR168036 6,9 -20+80 °C
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional	LVPAR168036 6,9 -20+80 °C LED DLS
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains	LVPAR168036 6,9 -20+80 °C LED DLS MLS
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface)	LVPAR168036 6,9 -20+80 °C LED DLS MLS GU10
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	LVPAR168036 6,9 -20+80 °C LED DLS MLS GU10 No
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source	LVPAR168036 6,9 -20+80 °C LED DLS MLS GU10 No No
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope	LVPAR168036 6,9 -20+80 °C LED DLS MLS GU10 No No
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source	LVPAR168036 6,9 -20+80 °C LED DLS MLS GU10 No No No No
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source Anti-glare shield	LVPAR168036 6,9 -20+80 °C LED DLS MLS GU10 No No No No No

54.00 mm

50.00 mm

Length

Height

Width	50.00 mm	
Chromaticity coordinate x	0.3123	
Chromaticity coordinate y	0.3282	
R9 Colour rendering index	1	
Beam angle correspondence	NARROW_CONE_90	
Survival factor	0.90	
Displacement factor	0.70	
LED light source replaces a fluorescent light source	No	
EPREL ID	522983,1368207,1842000,2505770	
Model number	AC32745,AC45674,AC57945,AC57945,AC57945,AC91856	

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	LED SPOT PAR16	
PDF	Declarations of conformity	LED PA16	
PDF	Declarations of conformity UKCA	LED PAR16	
	Photometric and lighting design files	Document name	
	IES file (IES)	PAR16 M3 80 36 6500K GU10	
	LDT file (Eulumdat)	PAR16 M3 80 36 6500K GU10	
	LDT file (Eulumdat) Light distribution curve type polar	PAR16 M3 80 36 6500K GU10 PAR16 M3 80 36 6500K GU10	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075096684	Folding box 1	52 mm x 52 mm x 60 mm	46.00 g	0.16 dm ³
4058075096691	Shipping box 10	270 mm x 114 mm x 72 mm	510.00 g	2.22 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.