

PRODUCT DATASHEET LED Star Classic B 40 Filament 4W 827 Clear B22d

LED Retrofit CLASSIC B | LED lamps, classic mini-candle shape



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Lower thermal output (compared with the standard reference product)
- Can be easily fitted instead of ordinary light bulbs
- Lower energy consumption than incandescent or halogen lamps

Product features

- Professional LED lamps for line voltage
- Not dimmable
- Good quality of light; color rendering index R_a: ≥ 80; constant chromaticity
- Lifetime up to 15,000 h





- Lamp made of glass

Clear B22d

TECHNICAL DATA

Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	40 W
Nominal current	32 mA
Type of current	AC
Inrush current	1.5 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	400
Max. lamp number on MCB B16 A	480
Power factor λ	> 0.50

Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	≤0.4



EPREL data spectral diagram PROF LEDr 2700K

Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	91.00 mm
Diameter	35.00 mm
Maximum diameter	35 mm
Product weight	20.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	65 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	B22d
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value / In development, data preliminary
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	E 1)
Energy consumption	4.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Stariuarus	
Photobiological safety group acc. to EN62778 Description of the Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations)	RG0 west efficiency)
Photobiological safety group acc. to EN62778 Denergy efficiency class (EEC) on a scale of A (highest efficiency) to G (low country-specific categorizations	west efficiency)
Photobiological safety group acc. to EN62778 Description of the Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low).	
Photobiological safety group acc. to EN62778 Description of the Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations ILCOS	west efficiency) DRBB/C-7-827-220/240-B22d-35
Photobiological safety group acc. to EN62778 Description of the Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations) LCOS Order reference	west efficiency) DRBB/C-7-827-220/240-B22d-35
Photobiological safety group acc. to EN62778 Country-specific categorizations ILCOS Order reference OGISTICAL DATA Temperature range at storage	west efficiency) DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82
Photobiological safety group acc. to EN62778 Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations ILCOS Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015	west efficiency) DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82
Photobiological safety group acc. to EN62778 Photobiological safety group acc. to EN62778 Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations ILCOS Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used	DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82 -20+80 °C
Photobiological safety group acc. to EN62778 Description of the Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations) ILCOS Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional	DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82 -20+80 °C LED
Photobiological safety group acc. to EN62778 Description of the Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations) ILCOS Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional	DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82 -20+80 °C LED NDLS
Photobiological safety group acc. to EN62778 Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations ILCOS Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains	DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82 -20+80 °C LED NDLS MLS
Photobiological safety group acc. to EN62778 Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations ILCOS Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface)	DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82 -20+80 °C LED NDLS MLS B22d
Photobiological safety group acc. to EN62778 Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations ILCOS Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82 -20+80 °C LED NDLS MLS B22d No
Photobiological safety group acc. to EN62778 Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations ILCOS Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source	DRBB/C-7-827-220/240-B22d-35 LEDSCLB40 4W/82 -20+80 °C LED NDLS MLS B22d No No

SINGLE_VALUE

0 W

0 W

Yes

Correlated colour temperature type

Networked standby power for CLS

Claim of equivalent power

Standby power

Length	91.00 mm
Height	35.00 mm
Width	35.00 mm
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.420
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.40
LED light source replaces a fluorescent light source	No
EPREL ID	1403414,523194
Model number	AC32383,AC24340,AC32383

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name		
PDF	Declarations of conformity	LED lamps CLA,B,G,P		
	Photometric and lighting design files	Document name		

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075437166	Folding box 1	36 mm x 49 mm x 145 mm	32.00 g	0.26 dm ³
4058075605008	Shipping box 6	129 mm x 111 mm x 120 mm	220.00 g	1.72 dm ³
4058075437173	Shipping box 10	201 mm x 111 mm x 120 mm	393.00 g	2.68 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Clear B22d