

# PRODUCT DATASHEET Vintage 1906 Globe 35 Filament 4W 824 Gold E27

Vintage 1906® LED | LED lamps, vintage edition



#### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lamps with innovative LED "filament" technology

#### Product features

- LED lamps for line voltage
- Lamp made of glass
- Lifetime up to 15,000 h





- Beam angle: up to  $360^{\circ}$
- Good quality of light; color rendering index  $\rm R_{a\!c} \geq 80$ ; constant chromaticity

## TECHNICAL DATA

## Electrical data

Nominal wattage	4 W
Construction wattage	4.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	35 W
Nominal current	32 mA
Type of current	AC
Inrush current	1.5 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	400
Max. lamp number on MCB B16 A	480
Power factor $\lambda$	> 0.40

### Photometrical data

Luminous flux	410 lm
Nominal useful luminous flux 90°	410 lm
Luminous efficacy	102 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm Comfort Light
Color temperature	2400 K
Color rendering index Ra	80
Light color	824
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9



LISO spectral power distribution 2700K CRI80 v1

# Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	168.00 mm
Diameter	124.00 mm
Maximum diameter	124 mm
Product weight	100.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	65 °C

## Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

## Capabilities

Dimmable	No
----------	----

## Certificates & Standards

Energy e	fficiency class	F 1)

Energy consumption	4.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Country-specific categorizations

ILCOS	DRAG/C-4/824-220/240-E27-124
Order reference	1906LEDGLOBE 4W

## LOGISTICAL DATA

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Networked standby power for CLS	0 W
Claim of equivalent power	Yes
Length	168.00 mm
Height	124.00 mm
Width	124.00 mm
Chromaticity coordinate x	0.494
Chromaticity coordinate y	0.424
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.40

LED light source replaces a fluorescent light source	No
EPREL ID	1403175,523040
Model number	AC32403,AC24351

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

### DOWNLOAD DATA

	Documents and certificates	Document name		
POF	Declarations of conformity	LED lamps CLA,B,G,P		
	Photometric and lighting design files	Document name		
	Spectral power distribution	LISO spectral power distribution 2700K CRI80 v1		

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899962071	Folding box 1	140 mm x 140 mm x 236 mm	211.00 g	4.63 dm <sup>3</sup>
4052899962569	Shipping box 4	291 mm x 291 mm x 251 mm	1112.00 g	21.25 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.