

# PRODUCT DATASHEET HALOSTAR PRO 15 W 12 V G4

HALOSTAR® PRO | Low-voltage halogen lamps with pin base



### Areas of application

- General illumination
- Kitchen lighting
- Lighting for reading
- Entrance lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Outdoor applications only in suitable luminaires

# **Product benefits**

- Brilliant accent lighting
- Significantly lower CO<sub>2</sub> emissions compared to standard version
- High luminous efficacy compared with standard lamps
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

#### **Product features**

- Average life: 4,000 h
- 100 % dimmable



- Color rendering index Ra: 100
- IRC technology


# TECHNICAL DATA

# Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	20 W
Nominal current	1.67 A

### Photometrical data

Luminous flux	220 lm	
Luminous efficacy	14 lm/W	
Light color (designation)	Warm White	
Color temperature	2800 K	
Color rendering index Ra	100	
Light color	1028	
UV protection	Yes	



# Light technical data

Starting time 0.0 s
---------------------

# Dimensions & Weight

Overall length	33.00 mm
Light center length (LCL)	22,0 mm
Diameter	10,0 mm
Product weight	1.1 g

# Lifespan

	5000
Number of switching cycles	50000
Additional product data	
Base (standard designation)	G4
Mercury-free	Yes
Capabilities	
Dimmable	Yes
Burning position	Any
Certificates & Standards	
Energy efficiency class	G
Energy consumption	15.00 kWh/1000h
Country-specific categorizations	
ILCOS	HSGT/C/UBIB-14-12-G4-10/22
Order reference	64423 ECO
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G4
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	33.00 mm
Height	10,0 mm
Width	10,0 mm
Chromaticity coordinate x	0.452
Chromaticity coordinate y	0.409
Beam angle correspondence	SPHERE_360

714429

EPREL ID

Model number	AC35317
--------------	---------

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

# DOWNLOAD DATA

	Documents and certificates	Document name
POF	Declarations of conformity	CE Declaration HAL LOW VOLT

Photometric and lighting design files	Document name
Spectral power distribution	349619_HAL_IRC

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321317964	Folding box 1	70 mm x 23 mm x 25 mm	3.67 g	0.04 dm <sup>3</sup>
4008321317971	Shipping box 40	144 mm x 119 mm x 121 mm	190.00 g	2.07 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.