

## PRODUCT DATASHEET

### L 18 W/930

LUMILUX® DE LUXE T8 | Tubular fluorescent lamps 26 mm, with G13 bases



#### Areas of application

- Ideal where color rendering is an important factor
- Public buildings
- Shops
- Supermarkets and department stores
- Industry

#### Product benefits

- Natural colors

#### Product features

- Very good color rendering index
- Dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	18 W
Construction wattage	18.60 W
Nominal voltage	57 V
Nominal current	0.37 A

Photometrical data

Luminous flux	1100 lm
Luminous efficacy	59 lm/W
Light color (designation)	LUMILUX DE LUXE Warm White
Color temperature	3000 K
Color rendering index Ra	≥90
Light color	930
Rated LLMF at 2,000 h	0.96
Rated LLMF at 4,000 h	0.94
Rated LLMF at 6,000 h	0.93
Rated LLMF at 8,000 h	0.91
Rated LLMF at 12,000 h	0.91
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89



349632\_FL\_930

Dimensions & Weight

Overall length	604.00 mm
Length with base excl. base pins/connection	590,00 mm
Diameter	26.00 mm
Tube diameter	26 mm

Product weight	86.00 g
----------------	---------

### Lifespan

Service life	16000 h <sup>1)</sup>
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.50
Lifespan B50	20000 h

1) With preheat ECG

### Additional product data

Base (standard designation)	G13
Mercury content	3.0 mg

### Capabilities

Dimmable	Yes
----------	-----

### Certificates & Standards

Energy efficiency class	G
Energy consumption	19.00 kWh/1000h

### Country-specific categorizations

ILCOS	FD-18/930-E-G13-26/600
Order reference	L 18W/930

### Energy labelling regulation data acc EU 2019/2015





Lighting technology used	OTHER_FL
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	No
Color-tuneable light source	No

Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	604.00 mm
Height	26.00 mm
Width	26.00 mm
Chromaticity coordinate x	0,436
Chromaticity coordinate y	0,399
Beam angle correspondence	SPHERE_360
EPREL ID	546386
Model number	AC34161

### Safety advice

– In case of lamp breakage: [www.ledvance.com/brokenlamp](http://www.ledvance.com/brokenlamp)

### DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	EC Declaration of Conformity - 2021 9C1-4077902-EN-00 - T8 DE LUXE
	Certificates	EAC RU C-DE HA10.B.00671 16 08 2018 15 07 2023 Expert Sertifikaciya FL
	Certificates	EAC N RU D-DE.MU62.B.00801_20 02.03.2020-01.03.2025 Prommash Test - FL
Photometric and lighting design files		Document name
	Spectral power distribution	349632_FL_930

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300011264	Sleeve 1	605 mm x 27 mm x 27 mm	90.00 g	0.44 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300236452	Shipping box 25	646 mm x 151 mm x 153 mm	2696.25 g	14.92 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.