

## PRODUCT DATASHEET

### NIGHTLUX Hall White

Starters for single operation at 230 V AC ( ST 111, ST 171, ST 173) | Starters for single operation at 230 V AC



#### Areas of application

- For a very large range of uses
- Indoor and outdoor
- Entrances / Hallways
- Corridors

#### Product benefits

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and fast mounting on nearly every surface (adhesive tape or screws)
- Light direction individually adjustable
- Accessories for flexible mounting options included

#### Product features

- Integrated light and motion sensor
- Available in two housing colors
- Switch for Auto- or On/Off-Mode
- Type of protection: IP54



TECHNICAL DATA


Electrical data

Nominal wattage	0.25 W
Nominal voltage	4,5 V
Operating mode	Battery
Nominal current	55.000 mA
Type of current	DC

Photometrical data

Luminous flux	14 lm
Luminous efficacy	56 lm/W
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	> 80
Light color	840
Standard deviation of color matching	≤6 sdc <sub>m</sub>

Dimensions & Weight



Product weight	98.00 g
----------------	---------

Temperatures & operating conditions

Ambient temperature range	0...+25 °C
---------------------------	------------

Lifespan

Number of switching cycles	10000
----------------------------	-------

Additional product data

Mercury content	0.0 mg
-----------------	--------

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Type of protection	IP54
Standards	CE

Country-specific categorizations

Order reference	NIGHTLUX HALL W
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+50 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Length	195.00 mm
Height	25.00 mm
Width	140.00 mm

EQUIPMENT / ACCESSORIES

- Batteries included: 3x1.5 V LR03 (AAA)

Safety advice

- This product is not a toy. It should not be left unattended in the hands of children or operated by children.
- Not designed as a replacement for conventional lighting in private household.
- Battery Warning: Keep out of reach for children. Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075027206	Shipping box 6	163 mm x 154 mm x 210 mm	845.00 g	5.27 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.