

PRODUCT DATASHEET

QT-FIT5 2X14...35

QUICKTRONIC® FIT 5 | ECG for FL 16 mm



Areas of application

- Open-plan offices, corridors and storage rooms
- Public buildings
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Suitable for luminaires of protection class I
- Modernization of existing systems

Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50 Hz | 60 Hz
- Lamp start with optimum filament preheating

- Energy Efficiency Index EEI: A2
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Lamp operation: to EN 60929
- Safety: to EN 61347-2-3

TECHNICAL DATA

Electrical data

Nominal wattage	78.00 W
Nominal voltage	220...240 V
Input voltage DC	198...264 V
U-OUT (working voltage)	430 V
Mains frequency	50/60 Hz
Operating frequency	40...50 kHz

Light technical data

Starting time	2 s
---------------	-----

Dimensions & Weight

Length	280.00 mm
Mounting hole spacing, length	270,0 mm
Width	30.00 mm
Height	21.00 mm
Cable cross-section, input side	0.5...1.5 mm ² 1)
Cable cross-section, output side	0.5...1.5 mm ² 1)
Product weight	181.00 g

1) Solid leads

Colors & materials

Casing material	Metal
Body material	Metal

Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % 1)

1) Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	50000 h
--------------	---------

Capabilities

Dimmable	No
Max. cable length to lamp/LED module	2.0 m / 1.0 m
Suitable for fixtures with prot. class	I
Suitable for emergency lighting	No
End of lamp life safety shutdown	EOL T.2








Certificates & Standards

Approval marks – approval	VDE / ENEC 10 / VDE-EMC
Standards	Acc. to EN 61347-2-3/IEC 61347-2-3 / Acc. to EN 55015:2006 + A1:2007 + A2:2009 / Acc. to EN 61000-3-2/IEC 61000-3-2 / Acc. to EN 61547/IEC 61547
Protection class	1
Type of protection	IP20
Energy efficiency class	A2 BAT
EEI – Energy Label	A2 BAT

LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	592456_EAC QT-FIT5
	Declarations of conformity	339525_Declaration of Conformity (GB)
	Certificates	339586_VDE-Marks approval
	Certificates	683441_ENEC-Marks approvals
	Certificates	339588 EMC-Marks approval
	Certificates	554891_EAC PT family
CAD/BIM files		Document name
	CAD data 3D PDF	339600_CAD QT-FIT5

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321971258	Unpacked 1		181.00 g	
4008321971265	Shipping box 20	303 mm x 101 mm x 159 mm	3786.00 g	4.87 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.