

PRODUCT DATASHEET

LS AY VAL -CSD/P4/P

Connectors for RGB LED Strips | Connectors for RGB LED Strips



Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	24 V
Nominal current	3000 mA

Dimensions & Weight

Length	27.0 mm
Width	17.0 mm
Height	7 mm
Product weight	8.00 g

Colors & materials

Product color	Transparent/Black
---------------	-------------------

Temperatures & operating conditions

Ambient temperature range	-15...+50 °C
Temperature range in operation	-15...+50 °C


Certificates & Standards


Type of protection	IP65
--------------------	------

LOGISTICAL DATA

Temperature range at storage	-20...+85 °C
------------------------------	--------------

DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	CE declaration LS AY VAL

Tender texts		Document name
	Tender documents	Connectors for RGB LED Strips CSDP4P-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075407923	BAG 2	80 mm x 120 mm x 5 mm	17.00 g	0.05 dm ³
4058075407930	Shipping box 100	120 mm x 100 mm x 120 mm	898.00 g	1.44 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075407947	Shipping box 1,000	525 mm x 140 mm x 270 mm	9371.00 g	19.85 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.