

PRODUCT DATASHEET TruSys® PFM ENERGY RAIL 8P 1500

TruSys® PERFORMANCE ENERGY RAIL 8 POLE | 8-pole mounting rail



Areas of application

- Industry halls, high rack warehouse, garages, hardware stores

Product benefits

- Simple installation
- High flexibility thanks to two available lengths (1500 mm, 3000 mm and 1500 mm end rail)

Product features

- Through wired with 8 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	1650 mm
Width	70.2 mm
Height	38.8 mm
Product weight	1630.00 g



Materials & Colors

Product color	White			
Application & Mounting				
Ambient temperature range	-25+60 °C			
Type of protection	IP20			
Mounting type	Surface			
Mounting location	Ceiling			
With light source	No			
Replaceable light source	No			

CE

EQUIPMENT / ACCESSORIES

- Various accessories available

DOWNLOAD DATA

Standards

	Documents and certificates	Document name
PDF	User instruction / safety instructions	TRUNKING SYSTEM PFM EM

CAD/BIM files	Document name
CAD STEP 3D	TRUSYS PFM ER 1500

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.