

PRODUCT DATASHEET LinearLED Mobile Battery 200

Linear LED Mobile | Undercabinet luminaire for flexible mounting, with motion sensor, battery-powered



Areas of application

- For a very large range of uses
- For indoor use only
- Shelves, furniture integration or under cabinet mounting

Product benefits

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and quick installation

Product features

- Housing material: aluminum
- Integrated light and motion sensor
- Switch for Auto- or On/Off-Mode



TECHNICAL DATA

Electrical data

| Nominal wattage | 1.90 W |
|-------------------------------------------------------------|--------|
| Nominal voltage | 6 V |
| Mains frequency | 0 Hz |
| Nominal current | 870 mA |
| Max. number of luminaires per miniature circuit breaker C10 | - |
| Protection class | III |

Photometrical data

| Luminous flux | 90 lm |
|--------------------------------------|------------|
| Luminous efficacy | 47 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | ≤6 sdcm |

Dimensions & Weight

| Length | 214.00 mm |
|----------------|-----------|
| Width | 48.00 mm |
| Height | 18.00 mm |
| Product weight | 250.00 g |



PG Linear LED Mobile 200 MiPRC

Materials & Colors

| Product color | White |
|-----------------|----------|
| Housing color | White |
| Body material | Aluminum |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|------------------------------|--------------------|
| Temperature range at storage | -30+70 °C |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Cabinet undersides |
| Application environment | Indoor |
| With light source | Yes |
| Replaceable light source | No |

Lifespan

| Lifespan L70/B50 at 25 °C | 25000 h ¹⁾ |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 25000 h ¹⁾ |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Sensor

| Type of sensor | Motion |
|-------------------|------------------------|
| Sensor technology | Passive infrared (PIR) |

BATTERY

| Type of Battery | Alkaline |
|------------------------------|----------|
| Battery size [GMS] | AA |
| Number of included batteries | 4 |
| Nominal voltage of battery | 1.5 V |

Certificates & Standards

| Standards | CE / EAC / UKCA |
|------------------------------------------------------|-----------------|
| Luminaire with limited surface temperature, "D sign" | No |
| Replaceable light source (EPREL) | Not replaceable |

Additional product data

| Number of illuminants empty |
|-----------------------------|
|-----------------------------|

EQUIPMENT / ACCESSORIES

- Batteries included: 4x 1.5 V LR6 (AA)
- All required accessories included

Safety advice

- This product is not a toy. It should not be left unattended in the hands of children or operated by children.
- Not designed as a replacement for conventional lighting in private household.
- Battery Warning: Keep out of reach for children. Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|----------------------------|---------------------|
| PDF | Declarations of conformity | LINEARLED MOBILE WT |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075226838 | Blister 1 | 22 mm x 140 mm x 400 mm | 290.00 g | 1.23 dm ³ |
| 4058075226845 | Shipping box 6 | 413 mm x 161 mm x 158 mm | 1904.00 g | 10.51 dm ³ |
| 4058075226852 | Shipping box 36 | 500 mm x 430 mm x 330 mm | 12003.00 g | 70.95 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.