

# PRODUCT DATASHEET ENDURA Classic Calice Wall E27

ENDURA CLASSIC CALICE | Stainless steel luminaires with glass diffuser



#### Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

#### **Product benefits**

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

#### **Product features**

- Available with and without motion sensor
- Stainless steel housing
- Type of protection: IP44



## **TECHNICAL DATA**

# Electrical data


Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.50
Protection class	1
Operating mode	Mains voltage

# Photometrical data

Standard deviation of color matching	< 6 sdcm
--------------------------------------	----------

# Dimensions & Weight

Length	161.00 mm
Width	120.00 mm
Height	290.00 mm
Product weight	900.00 g



## Materials & Colors

Product color	Steel
Housing color	Steel
Body material	Stainless steel
Cover material	Glass
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C

Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
With light source	No
Replaceable light source	No

## Certificates & Standards

	Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"		No

## Additional product data

		Product remark	Maximum bulb wattage: 60 W
--	--	----------------	----------------------------

#### **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	ENDURA CLASSIC CALICE
POF	Legal information	Legal insert I-Outdoor
PDF	Declarations of conformity	ENDURA CLASSIC CALICE WALL E27 ST
POF	Declarations of conformity UKCA	Fixed LUM without EMC

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075477957	Folding box	202 mm x 162 mm x 334 mm	1055.00 g	10.93 dm <sup>3</sup>
4058075477964	Shipping box 4	420 mm x 350 mm x 340 mm	4997.00 g	49.98 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.