

## FICHE PRODUIT LFP200M -G3-BL-06

LINEARlight FLEX® Protect ECO | Modules LED pour des applications professionnelles et industrielles



### Zones d'application

- Decorative applications
- Wall integration
- Backlighting of complex structures
- Path lighting
- Signage
- Suitable for outdoor use

### Avantages du produit

- Large selection of light colors
- Great design freedom thanks to flexibility and cuttability of module
- High-performance silicone for extremely long life and flexibility
- Simple connection thanks to premounted connectors
- Extraordinary design and high quality materials
- Toolless connection with the optional CONNECTsystem
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back

### Caractéristiques du produit

- Flexible and cuttable LED strip
- Luminous flux: up to 200 lm/m
- Type of protection: IP67



- Dimmable with PWM technology
- Fine White (3.5 SDCM)
- Salt mist proof

## DONNÉES TECHNIQUES

## DONNÉES ÉLECTRIQUES

|                              |                     |
|------------------------------|---------------------|
| Puissance nominale           | 24.50 W             |
| Puissance nominale par mètre | 4.1 W               |
| Tension nominale             | 24 V                |
| Plage de tension             | 23...25 V           |
| Tension inverse              | 25 V                |
| Type de courant              | Courant direct (DC) |
| Intensité nominale           | 1020,000 mA         |

## Données photométriques

|  |         |
|--|---------|
| Total des flux lumineux utiles [PICOS] | 290 lm  |
| Efficacité lumineuse                   | 12 lm/W |
| Flux lumineux                          | 290 lm  |
| Flux lumineux par mètre                | 48 lm   |
| Couleur de la LED                      | Bleu    |
| Teinte de couleur (désignation)        | Bleu    |
| Longueur d'onde nominale dominante     | 467 nm  |

## Données techniques légères

|                              |          |
|------------------------------|----------|
| Angle de rayonnement         | 120 °    |
| Angle de faisceau évalué     | 120.00 ° |
| Temps d'amorçage             | < 0.5 s  |
| Temps de préchauffage (60 %) | 0,00 s   |

## LED MODULE INFORMATION

|                             |     |
|-----------------------------|-----|
| Nombre de LED par mètre     | 33  |
| Nombre de LED par module    | 200 |
| Nombre de LED par composant | 5   |

## DIMENSIONS ET POIDS

|  |          |
|--|----------|
| Longueur                                 | 6000 mm  |
| Longueur – composant seul                | 150 mm   |
| Longueur de câble                        | 500.000  |
| Largeur                                  | 11,10 mm |
| Largeur (y compris les luminaires ronds) | 11.10 mm |

|                                       |                      |
|---------------------------------------|----------------------|
| Hauteur                               | 4,80 mm              |
| Hauteur (luminaires cycliques inclus) | 4.80 mm              |
| Section du câble au primaire          | 0,34 mm <sup>2</sup> |
| Section du conducteur                 | 0.34 mm <sup>2</sup> |
| LED pitch                             | 30,0 mm              |
| Poids du produit                      | 390,00 g             |

## COULEURS ET MATÉRIAUX

|                       |          |
|-----------------------|----------|
| Matériau de fermeture | Silicone |
|-----------------------|----------|

## TEMPÉRATURES ET CONDITIONS DE FONCTIONNEMENT

|  |                           |
|--|---------------------------|
| Plage de température ambiante                | -20...+50 °C              |
| Température maximale au point de test        | 70 °C                     |
| Plage de température au point T <sub>c</sub> | -20...70 °C <sup>1)</sup> |
| T° fonctionnement confit norme IEC 62717     | 35 °C <sup>2)</sup>       |

1) Au point T<sub>c</sub>

2) Classé T<sub>p</sub>. Le point T<sub>p</sub> coïncide avec le point T<sub>c</sub> - marqué sur l'appareil

## DONNÉES SUPPLÉMENTAIRES SUR LE PRODUIT

|  |  |
|--|--|
| Notes bas de page util. uniquem. produit | Modules parfaitement adaptés aux convertisseurs LED OSRAM OPTOTRONIC® (voir tableau correspondant) / Pour obtenir les données photométriques actuelles et les informations sur la sécurité, l'installation et l'application, voir <a href="http://www.osram.com/led-systems/">http://www.osram.com/led-systems/</a> Tous les paramètres techniques s'appliquent au module entier. En raison de la complexité de la production des LED, les valeurs techniques indiquées sont des valeurs statistiques. Les valeurs réelles de chaque lampe peuvent différer de ces valeurs |
|--|--|

## CAPACITÉS

|                              |                    |
|------------------------------|--------------------|
| Gradable                     | Oui                |
| Gradateur                    | PWM                |
| Type d'installation          | Montage en surface |
| Plus petit rayon de courbure | 50 mm              |
| Auto-adhésif                 | Oui                |

## CERTIFICATS ET NORMES

|                        |                                      |
|------------------------|--------------------------------------|
| Normes                 | CE / EAC / Composant reconnu UL 8750 |
| Type de protection     | IP67                                 |
| Consommation d'énergie | 27.00 kWh/1000h                      |

## DONNÉES LOGISTIQUES

|                                  |              |
|----------------------------------|--------------|
| Plage de température de stockage | -40...+85 °C |
|----------------------------------|--------------|





## ÉQUIPEMENT / ACCESSOIRES

- Simplified connection with optional matching CONNECTsystem
- Quick installation with optional SLIM TRACK System
- Perfectly matched to OPTOTRONIC 24 V electronic control gears

## INFORMATIONS SUPPLÉMENTAIRES SUR LE PRODUIT

- Some LED modules are equipped with a self-adhesive tape for attaching the LED module to suitable materials, such as aluminum profiles, which must be clean and free of oil or silicone coatings, as well as other dirt/dust particles. The adhesive tape is intended for single use and if removed may damage the material to which it is stuck and the LED module itself, which must then be scrapped. Use the adhesive tape when the installation material temperature is in the 18 °C...35 °C range. Complete adhesion takes up to 72 h.
- LED modules are designed for static installations in accordance with IPC 6013C – Use A. Take material vibrations, repetitive torsion, and elongation/compression into account.
- If the operating environment covers a broad temperature range (e.g. outdoor applications) and the operating length is longer than 2 m, the use of adequate mounting surfaces is required. The use of an additional thicker adhesive tape between LED module and mounting surface is also recommended in order to absorb the stress of any mismatch in expansion. Assure enough space for module expansion with increasing temperature.
- The manufacturer is not responsible for damage due to chemical corrosion. The user must provide suitable protection against corrosive agents such as moisture and condensation and any other harmful elements/compounds. Make certain to avoid corrosive atmospheres. According to the current state of LED technology, hydrogen sulfide (H<sub>2</sub>S) causes accelerated corrosion which leads to shortened lifetime or premature failure. Sources of H<sub>2</sub>S may be rubber, foam rubber, soft-foam tapes, rubber-based sealing, natural sources (e.g. sulfur springs), etc. To avoid H<sub>2</sub>S from sulfur-vulcanized rubber use silicon-based materials or peroxide-crosslinked rubber instead. Follow the recommendations in the material datasheet of the rubber supplier.
- IP00 LED modules, as manufactured, have no conformal coating and therefore offer no inherent protection against corrosion. Conformal coating treatment is possible, however materials must be selected properly in order to avoid product damage or impaired performance; the user must also completely seal the cut parts (ends/edges).
- For applications involving exposure to humidity and dust the module must be protected by a fixture or housing with a suitable IP protection class.
- Consult OSRAM Technical Service for further advice.
- Only a qualified electrician may install the module.
- Handle with care and ensure that there is no mechanical product damage, including damage to invisible internal electronics parts.
- Exceeding maximum operating and storage temperature ratings can reduce the expected lifetime or even destroy the LED module. The temperature of the LED module must be measured at the T<sub>c</sub>-point in accordance with EN 60598-1 under steady-state conditions, considering the worst case; drive all channels at 100 % power. Refer to the product drawing for the exact location of the T<sub>c</sub>-point.
- Exceeding the maximum ratings for the operating voltage causes hazardous overload and will likely destroy the LED module.
- Installation of LED modules and connection to the power supply must comply with all applicable electrical and safety standards.
- Observe correct polarity and wiring diagrams! Incorrect polarity or wrong wiring can cause unpredictable permanent damage or even failure of the product.
- Never exceed the maximum operable length, including daisy-chaining connections.
- Always ensure electrical isolation between the LED module and the mounting surface, especially in the vicinity of connections or cut ends.
- IP00 LED modules are ESD-sensitive; take adequate precautions during installation and operation of the products.
- Use only SELV LED drivers in accordance with applicable lighting standards and LED module ratings. In order to safely operate OSRAM LED modules it is necessary to supply them with an electronically stabilized power supply providing protection against short circuits, overload and overheating. To simplify the approval process of the luminaire/installation, the electronic power supplies control gear for LED modules must bear the CE and ENEC marking. In Europe the Declarations of Conformity must include at least the following standards: EN 61347-2-13, EN 55015, EN 61547 and EN 61000-3-2. ENEC certification will be based on EN 61347-2-13 and EN 62384. OSRAM OPTOTRONIC LED drivers comply with all relevant standards and guarantee safe operation; see the relevant brochure for more detailed information about OSRAM OPTOTRONIC.
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

## TÉLÉCHARGEMENTS

| Documents et certificats   |                            | Nom du document                      |
|--|----------------------------|--------------------------------------|
|  | Déclarations de conformité | Manufacturers Decalration LFP200M G3 |
|  | Déclarations de conformité | Declaration of Conformity LFP200M G3 |
| Photométrie et fichiers pour études d'éclairage                                  |                            | Nom du document                      |
|  | Fichier IES (IES)          | IES LFP200M-G3-BL-06                 |
|  | Fichier LDT (Eulumdat)     | Eulumdat LFP200M-G3-BL-06            |

## DONNÉES LOGISTIQUES

| Code produit  | Unité d'emballage (Pièces/Unité) | Dimensions (longueur x largeur x hauteur) | Poids approximatif | ' Volume              |
|---------------|----------------------------------|---|--------------------|-----------------------|
| 4052899500525 | Etui carton fermé<br>1           | 353 mm x 349 mm x 32 mm                   | 869.00 g           | 3.94 dm <sup>3</sup>  |
| 4052899500532 | Carton de regroupement<br>8      | 365 mm x 286 mm x 366 mm                  | 7338.00 g          | 38.21 dm <sup>3</sup> |

Le code produit mentionné décrit la petite quantité d'unité qui peut être commandée. Une unité peut contenir un ou plusieurs produits. Lorsque vous passez la commande, merci de bien vouloir entrer une unité ou un multiple d'une unité.

## AVERTISSEMENT

Sous réserve de modifications. Sauf erreur ou omission. Veuillez à toujours utiliser la version la plus récente.