# **LEDVANCEUS.COM**





Environmentally preferable to traditional technologies, these Cutoff Wall Packs offer dual selectability and an optional sensor for further energy savings. The UV stabilized polycarbonate lens, IK08 rating, and 10-year warranty ensure a long lasting and robust luminaire perfect for lighting outdoor corridors, walkways, and stairwells.

### SUPERIOR CLASS

















# LEDVANCEUS.COM



LEDVANCE LLC 181 Ballardvale Street, Suite 203 Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828)

# **SUPERIOR CLASS CUTOFF WALL PACK 6A**

Item Number	Ordering Abbreviation	Wattage (W)	Input Voltage (V)	Dimming	CRI	Color Temperature (CCT)	Distribution	Total Fixture Lumens	LPW	MTO*
62723	WALPAKC6AS080UNVD8SC2T2BZP	45/65/80	120-277V	0-10V	>80	3000K/4000K/5000K	Type II	6300/9100/11,200	Up to 140	MTO
62725	WALPAKC6AS080UNVD8SC2T4BZP	45/65/80	120-277V	0-10V	>80	3000K/4000K/5000K	Type IV	6300/9100/11,200	Up to 140	-
62724	WALPAKC6AS120UNVD8SC2T2BZP	75/95/120	120-277V	0-10V	>80	3000K/4000K/5000K	Type II	10,500/13,300/16,800	Up to 140	MTO
62726	WALPAKC6AS120UNVD8SC2T4BZP	75/95/120	120-277V	0-10V	>80	3000K/4000K/5000K	Type IV	10,500/13,300/16,800	Up to 140	-

<sup>\*</sup>Made To Order

#### **CONTRACTOR BENEFITS**

- Standard backbox form factor to easily replace traditional luminaires
- Dual selectability for limited SKU quantity and flexibility on the job site
- Easily installed on junction boxes or as side conduit mount

### **BENEFITS AND FEATURES**

- DLC 5.1 Premium listing and CCT and lumen selectability provide high energy efficacy and optimize this product for utility rebates
- Traditional sizes allow seamless replacement of existing luminaires
- IoT compatibility allows for customizable light
- Up to 140 LPW
- 3000K, 4000K and 5000K color temperature selectable
- CRI >80
- Two selectable wattage options: 45/65/80W and 75/95/120W
- Type II and Type IV cutoff distribution
- Energy savings up to 78%

## SIZE

Luminaire	Length	Width	Height	Weight
Desciption	(inches)	(inches)	(inches)	(lbs)
80W/120W	14.4	7.8	9.3	8.3/8.5



LEDVANCE is a registered trademark. All other trademarks are those of

their respective owners. Specifications subject to change without notice.

Scan the QR tag to view or download additional product information

