

## SYLVANIA UltraLED™ RT Downlight Dual Selectable Make all the right choices with one dynamic product

Ideal for commercial buildings, offices, schools, hospitality or retail applications, the SYLVANIA UltraLED™ RT Downlight Dual Selectable is the new generation of professional downlight luminaires. Two switches in the back let you choose the color temperature and lumen output best for your application. Make the best choice with one dynamic product. Lightweight spinning aluminium construction makes installation easy while maintaining heat distribution. Its sleek design makes any environment look modern. The dual selectable family is compatible with an emergency battery back-up (field installable) that helps keep spaces safe even when electricity is out.

## **Benefits and Features**

- Spinning aluminum construction
- Optimized for new construction and retrofits replacing pin-based compact fluorescents
- CCT selectable light enabled through the switch located on the base of the product (4 light colors in the same product)
- Lumen selectable enabled through the switch located on the base of the product (3 lumen levels in the same product)
- ENERGY STAR® listed to maximize rebate opportunities
- Emergency Battery Backup Ready (field installable)
- Wet Rated
- Uniform, glare free illumination
- Energy savings up to 36%

For more information, visit www.ledvanceUS.com/luminaires

















## Ordering Information

## **SYLVANIA UltraLED™ RT Downlight Dual Selectable**

| Item<br>Number | Ordering<br>Abbreviation | Power<br>(W) | Base<br>Type | Traditional<br>Replacement<br>(W) | Input<br>Voltage<br>(V) | Average<br>Life<br>(hrs) | ССТ                      | Typical<br>Lumens<br>(lm) | CRI | Power<br>Factor | Bulb<br>Finish | Case<br>Qty | ENERGY<br>STAR® | T24 |
|----------------|--------------------------|--------------|--------------|-----------------------------------|-------------------------|--------------------------|--------------------------|---------------------------|-----|-----------------|----------------|-------------|-----------------|-----|
| 65686          | RT4S700UNVD9275A         | 7/8/9        | Hardwire     | 8/11/14                           | 120-277                 | 50,000                   | 2700K                    | 500/600/700               | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65687          | RT4S700UNVD9SC85A        | 7/8/9        | Hardwire     | 8/11/14                           | 120-277                 | 50,000                   | 3000/3500/<br>4000/5000K | 500/600/700               | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65688          | RT6S900UNVD9275A         | 7/9/11       | Hardwire     | 8/14/15                           | 120-277                 | 50,000                   | 2700K                    | 500/700/900               | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65689          | RT6S900UNVD9SC85A        | 7/9/11       | Hardwire     | 8/14/15                           | 120-277                 | 50,000                   | 3000/3500/<br>4000/5000K | 500/700/900               | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65690          | RT6S2000UNVD9SC85A       | 14/18/24     | Hardwire     | 15/23/27                          | 120-277                 | 50,000                   | 3000/3500/<br>4000/5000K | 1100/1500/2000            | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65691          | RT8S3300UNVD9SC85A       | 25/29/35     | Hardwire     | 2x17/2x19/<br>2x23                | 120-277                 | 50,000                   | 3000/3500/<br>4000/5000K | 2400/2800/3300            | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65692          | RT10S4000UNVD9SC85A      | 32/37/43     | Hardwire     | 2x23/2x24/<br>2x27                | 120-277                 | 50,000                   | 3000/3500/<br>4000/5000K | 3000/3500/4000            | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65693          | RT4S1000UNH9SC85A        | 7/9/12       | Hardwire     | 8/11/14                           | 120-347                 | 50,000                   | 2700/3000/<br>3500/4000K | 600/800/1000              | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65694          | RT6S2000UNH9SC85A        | 10/18/23     | Hardwire     | 15/23/27                          | 120-347                 | 50,000                   | 2700/3000/<br>3500/4000K | 900/1600/2000             | >90 | >90             | Frosted        | 4           | Yes             | Yes |
| 65695          | RT8S3000UNH9SC85A        | 20/28/34     | Hardwire     | 27/2x17/<br>2x23                  | 120-347                 | 50,000                   | 2700/3000/<br>3500/4000K | 1850/2500/3000            | >90 | >90             | Frosted        | 4           | Yes             | Yes |



Scan the QR tag to view or download additional product information

LEDVANCE LLC 181 Ballardvale Street, Suite 203 Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828) www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks. All other trademarks are those of their respective owners. Licensee of product trademark SYLVANIA in general lighting. Specifications subject to change without notice.



