



SYLVANIA LEDlescent™ T8 Ballast-Free Lamps

Let the classroom shine

Introducing the 5 CCT Selectable family of LEDlescent linear and CURVALUME® Ubend lamps. LEDlescent UL Type B lamps do not require a ballast and therefore eliminate any compatibility issues. This family includes 2-foot, 3-foot, and 4-foot lamps as well as the Ubend option with five color temperatures (3000K, 3500K, 4100K, 5000K, 6500K). This provides flexibility of color choice at the time of installation and reduction inventory on the shelf and the truck. These lamps are DLC 5.1 having 50,000 hours of life and offer a 5-year warranty.

Benefits and Features

- Frosted glass optics with shatter-resistant PET coating
- For use with shunted and non-shunted sockets therefore no socket change is needed
- No polarity; can be installed in either direction, saving time (costs) in installation
- No risk of electrical arcing between the lamp pins and the lamp holders
- Suitable for dry and damp locations – not for use where directly exposed to water
- G13 medium bi-pin base
- Suitable for open and enclosed fixtures
- Dimmable using some 120V phase cut dimmers (tested and passed with LUTRON NTELV-300, NTELV-600, MAELV-600 and CTELV-303P dimmers).
- No warm-up time, instant-on with full light output and stable lamp to selected lamp color
- Efficacy ranging from 129 to 150 LPW
- CRI >80
- Offered in 8, 12 & 15 watts
- Available beam angle: 220° (Linear), 170° (Ubend)
Light emitting angle 340° (Linear), 300° (Ubend)
- Energy savings up to 53%

Contractor Benefits

- One lamp, 5 different CCTs from which to choose minimizes SKUs and inventory
- Available in 2-foot, 3-foot, 4-foot, and Ubend lengths
- Direct-wire can be used to replace T8 or T12 by bypassing the existing ballast

For more information, visit www.ledvanceUS.com



Ordering Information

SYLVANIA LEDiescent™ T8 Ballast-Free Lamps

Item Number	Ordering Abbreviation	Lamp Length	Lamp Power (W)	Initial Lumens @4100K (lm)	Efficacy (LPW)	Selectable Color Temp. (CCT)	CRI	Beam Angle (°)	Package Qty	DLC
41876	LED8T8L24FGPDIM8SC12BF	2ft	8	1050	131	3000K/3500K/4100K/5000K/6500K	>80	220	25	5.1
41877	LED12T8L36FGPDIM8SC12BF	3ft	12	1550	129	3000K/3500K/4100K/5000K/6500K	>80	220	25	5.1
41878	LED12T8L48FGPDIM8SC12BF	4ft	12	1800	150	3000K/3500K/4100K/5000K/6500K	>80	220	25	5.1
41879	LED15T8UFGPDIM8SC12BF	U-Bend	15	2000	133	3000K/3500K/4100K/5000K/6500K	>80	170	10	5.1



Scan the QR tag to view
or download additional
product information

LEDVANCE LLC
181 Ballardvale Street, Suite 203
Wilmington, MA 01887 USA
Phone 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks. All other trademarks are those of their respective owners.
Licensee of product trademark SYLVANIA in general lighting. Specifications subject to change without notice.



SCAN TO FOLLOW US
ON SOCIAL MEDIA

