



Product Serv

# CERTIFICATE

No. U6 097386 0146 Rev. 00

**Holder of Certificate:** LEDVANCE GmbH

Parkring 29-33  
85748 Garching  
GERMANY

**Certification Mark:**



**Product:**

**Fixed general purpose luminaires  
LED water proof light**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:**

704022106507-00

**Date,**

2021-03-17

( Yin Ji )

# CERTIFICATE

No. U6 097386 0146 Rev. 00

**Model(s):**

- DP DALI 1200 18W 840 IP65 GY;
- DP DALI 1200 18W 865 IP65 GY;
- DP DALI 1200 32W 830 IP65 GY;
- DP DALI 1200 32W 840 IP65 GY;
- DP DALI 1200 32W 865 IP65 GY;
- DP DALI 1500 26W 840 IP65 GY;
- DP DALI 1500 26W 865 IP65 GY;
- DP DALI 1500 46W 830 IP65 GY;
- DP DALI 1500 46W 840 IP65 GY;
- DP DALI 1500 46W 865 IP65 GY;
- DP DALI 1500 58W 840 IP65 GY;
- DP DALI 1500 58W 865 IP65 GY

**Brand Name:** **LEDVANCE**



**Parameters:**

Rated voltage: 220-240V~  
 Rated frequency: 50/60Hz  
 Rated power: See model list  
 Protection class: Class I  
 Degree of protection: IP65  
 ta: See model list

Model	Rated power	ta
DP DALI 1200 18W 840 IP65 GY	18W	40°C
DP DALI 1200 18W 865 IP65 GY	18W	40°C
DP DALI 1200 32W 830 IP65 GY	32W	40°C
DP DALI 1200 32W 840 IP65 GY	32W	40°C
DP DALI 1200 32W 865 IP65 GY	32W	40°C
DP DALI 1500 26W 840 IP65 GY	26W	40°C
DP DALI 1500 26W 865 IP65 GY	26W	40°C
DP DALI 1500 46W 830 IP65 GY	46W	40°C
DP DALI 1500 46W 840 IP65 GY	46W	40°C
DP DALI 1500 46W 865 IP65 GY	46W	40°C
DP DALI 1500 58W 840 IP65 GY	58W	35°C
DP DALI 1500 58W 865 IP65 GY	58W	35°C

**Tested according to:** EN 60598-1:2015/A1:2018  
 EN 60598-2-1:1989  
 EN 60598-2-24:2013

**Production Facility(ies):** 101065