




LHT- 5/6/8/10K F1

Three Phase Hybrid Inverter

- 100% unbalanced output, each phase;
Max. output up to 50% rated power
- DC couple and AC couple to retrofit existing solar system
- Max. 10pcs parallel for on-grid and off-grid operation:
Support multiple batteries parallel
- Max. charging/discharging current of 37A
- High voltage battery, higher efficiency
- 6 time periods for battery charging/discharging
- Support storing energy from diesel generator
- Color LCD touch screen, IP65 protection

MODEL	LHT-5K F1	LHT-6K F1	LHT-8K F1	LHT-10K F1
Battery Input Data				
Battery Type	Li-Ion			
Battery Voltage Range (V)	160~700			
Max. Charging Current (A)	37			
Max. Discharging Current (A)	37			
Number of battery input	1			
Charging Strategy for Li-Ion Battery	Self-adaption to BMS			
PV String Input Data				
Max. DC Input Power (W)	6500	7800	10400	13000
Max. DC Input Voltage (V)	1000			
Start-up Voltage (V)	180			
MPPT Range (V)	150-850			
Full Load DC Voltage Range (V)	195-850	195-850	260-850	325-850
Rated DC Input Voltage (V)	600			
PV Input Current (A)	20+20			
Max. PV Isc (A)	30+30			
No.of MPP Trackers	2			
No.of Strings per MPP Tracker	1+1			
AC Output Data				
Rated AC Output and UPS Power (W)	5000	6000	8000	10000
Max. AC Output Power (W)	5500	6600	8800	11000
AC Output Rated Current (A)	7.6/7.3	9.1/8.7	12.2/11.6	15.2/14.5
Max. AC Output Rated Current (A)	8.4/8	10/9.6	13.4/12.8	16.7/16
Max. AC Current (A)	13	13	18	22
Max. Continuous AC Passthrough (A)	80			
Peak Power (off-grid)	1.5 time of rated power, 10 S			
Power Factor	0.8 leading to 0.8 lagging			
Output Frequency and Voltage	50/60Hz; 3L/N/PE 220/380, 230/400Vac			
Grid Type	Three Phase			
Total Harmonic Distortion (THD)	<3% (of nominal power)			
Generator input / Smart load / AC couple current (A)	7.6/40/7.6	9.1/80/9.1	12.2/80/12.2	15.2/80/15.2

MODEL	LHT-5K F1	LHT-6K F1	LHT-8K F1	LHT-10K F1
Efficiency				
Max. Efficiency	97.6%			
Euro Efficiency	97.0%			
MPPT Efficiency	99.9%			
Protection				
Integrated	PV Input Lightning Protection, Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge protection			
Output Over Voltage Protection	DC Type II/AC Type III			
General Data				
Size (mm), w/h/d	408x638x237			
Weight (kg)	30.5			
Installation Style	Wall-mounted			
Cooling	Smart cooling			
Protection Degree	IP65			
Noise Emission	<55 dB			
Communication with BMS	RS485; CAN			
Warranty	10 years			
Operating Temperature Range (°C)	-40~60°C, >45°C derating			
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			
Grid Regulation	VDE4105, IEC61727/62116, VDE0126, AS4777.2, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002, NBR16149/ NBR16150			