



VALUE CLASS

SIMPLIFYING YOUR WORK

- 3 CCTs and multiple wattages combined into both 2-foot and 4-foot versions
- Designed for fast, easy installation, the lens and LED light engine are removed as one unit - without tools - giving direct access to the wiring chamber
- Simple field installable PIR, Microwave, or LINK™ sensors
- Full edge-to-edge lens illumination



















ORDERING GUIDE

WRAP	FVL /	SXXX	UNH	D	8	SC7 /	XX/	WH/	Х
PRODUCT NAME	GENERATION	SELECTABLE WATTAGE	INPUT VOLTAGE	DIMMING	CRI	SELECTABLE CCT	SIZE	COLOR	OPTIONS
Wrap	FVL	S030 = 15/20/25/30W S050 = 30/40/50W	UNH = 120-347V	D = 0-10V Dimming	8 = 80+	SC7 = 3500/4000/5000K	24 = 2ft 48 = 4ft	WH = White	E = Emergency Back-up Battery

FEATURES



CONTROLS READY

 Easily accepts LEDVANCE LINK™ DLC approved Networked Lighting Control or standalone controls via 3.5mm receptacle no special wiring or electrician required.



BEHIND THE LENS SENSOR

 Can also accommodate a behind-thelens microwave sensor



INSTALLATION

- Integrated lens and LED tray allows for simple access to wiring and fast, efficient installation
- No tools needed to remove lens
- Surface or suspended mounted
- Included V-hooks
- Optional aircraft cables, mounting chains and end-to-end joiner brackets

LEDVANCE LLC

181 Ballardvale Street, Suite 203 Wilmington, MA 01887 USA

Phone: 1-800-LIGHTBULB (1-800-544-4828)

www.ledvanceUS.com

LEDVANCE is a registered trademark. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, inc. and any use of such marks by LEDVANCE LLC is under license. All other trademarks are those of their respective owners. Specifications subject to change without notice.



SCAN TO FOLLOW US ON SOCIAL MEDIA

EDGE-TO-EDGE LENS

- Diffused acrylic lens reaches across the entire front of the luminaire, providing edge-to-edge, smooth, even illumination
- Wide body at 5.16"





