

EFFICIENT LIGHTING UPGRADES FOR SCHOOLS AND OFFICES

DUALescent™ UL TYPE (A+B) LAMPS

SIMPLIFYING YOUR WORK

- CCT selectability enabled through switches located on the lamp aids in reduced inventory and greater job site flexibility.
- Flexible installation options, either as a Type A direct replacement on compatible T8 electronic ballasts or Type B direct wire to line voltage (SE/DE) to avoid incompatibility and ballast maintenance.
- Adjust brightness and achieve additional energy savings through 120V phase-cut dimming (Type B) or when paired with compatible 0-10V dimming ballast (Type A) with robust dimmer list.



ORDERING GUIDE

LED	XX	T8	FG	DIM	8	SC12	AB
LED	WATTAGE	LAMP TYPE	COLOR/FINISH	DIMMING	CRI	COLOR TEMP	OPERATION
LED = LED Lamp	12 = 12 Watts 15 = 15 Watts	T8	FG = Frosted Glass	DIM = Dimmable	8 = 82	SC12 = CCT Selectable (3000K/3500K/4100K/5000K/6500K)	AB = UL Type (A+B)

FEATURES



5CCT SELECTABLE

Aids in inventory reduction & greater job site flexibility.

FINISH/DISTRIBUTION

Frosted glass optic & LED placement result in even light, no hot spots
Beam angle: 200°;
Light emitting angle: 320°

INSTALLATION

Flexible installation options, either Type A direct replacement on compatible Instant start or programmed rapid start T8 ballasts or Type B direct wire to line voltage, 120-277V (SE/DE) to avoid incompatibility and ballast maintenance.

SAFETY

Patented internal safety circuit for Type B double-ended installation to prevent shock hazard (Recommended for new installations).

DIMMING

Adjust brightness & achieve additional energy savings through 120V phase-cut dimming (Type B) or when paired with compatible 0-10V dimming ballast (Type A) with robust dimmer list.

LEDVANCE LLC
181 Ballardvale Street, Suite 203
Wilmington, MA 01887 USA
Phone: 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

LEDVANCE is a registered trademark.
All other trademarks are those of their respective owners.
Specifications subject to change without notice.



SCAN TO FOLLOW US
ON SOCIAL MEDIA



Spec Sheet



Install Guide