

LEDVANCE

# LIGHT UP YOUR FACILITY!

## DUAL SELECTABLE UFO 5A

VALUE  
CLASS

### SIMPLIFYING YOUR WORK

- CONTROLS READY: easily accepts LEDVANCE LINK™ DLC approved Networked Lighting Control or standalone controls via screw-in receptacle
- Multiple mounting options for any installation
- Full line of accessories to meet all installation needs



## ORDERING GUIDE

UFO	5A	/SXXX	XXX	D	8	SC7	/XX
PRODUCT NAME	GENERATION	SELECTABLE WATTAGE	VOLTAGE	DIMMING	CRI	SELECTABLE COLOR TEMP	COLOR/FINISH
UFO = UFO	5A = Generation 5A	S200 = 100/150/200W S320 = 240/280/320W	UNH = 120-347V HUV = 277-480V	D = 0-10V Dimming	8 = >80 CRI	SC7= 3500/4000/5000K	WH= White BL = Black

## FEATURES

### INSTALLATION

Ships with hook to accommodate most applications. Weighs less than 9lbs and includes 6' power cord and 3' dimming cord.



### BATTERY BACKUP

Field installable 40W emergency battery backup unit

### ENVIRONMENT

Suitable for a number of applications with the IP65 and NSF splash zone rating. TAA listing allows it to be used on government projects. Available in either white or black housing.

**CONTROLS**  
READY

### CONTROLS READY

Easily accepts LEDVANCE LINK™ DLC approved Networked Lighting Control or standalone controls via 3.5mm receptacle no special wiring or electrician required.


## ACCESSORIES



**SURFACE/PENDANT MOUNT BRACKET**  
65613, 65614 (white)  
65702, 65703 (black)



**REMOTE**  
65623



**WIRE GUARD**  
65620, 65621



**POLYCARBONATE BOTTOM LENS**  
61432



**ALUMINUM REFLECTOR**  
65618, 65619



**POLYCARBONATE REFRACTOR**  
65616, 65617

\*Additional accessories can be found on spec sheet.

LEDVANCE LLC  
181 Ballardvale Street, Suite 203  
Wilmington, MA 01887 USA  
Phone: 1-800-LIGHTBULB (1-800-544-4828)  
www.ledvanceUS.com

LEDVANCE is a registered trademark.  
All other trademarks are those of their respective owners.  
Specifications subject to change without notice.



SCAN TO FOLLOW US  
ON SOCIAL MEDIA



Spec Sheet



Install Guide