


DIMMER COMPATIBILITY R50+R63+R80

BASIC INFORMATION:

1. WHAT IS THE PRODUCT CODE AND WHERE DO I FIND IT?





The product code describes the lamp type. It contains 7 letters and digits and is starting with "A". Below an example for the product code of the stamp of the lamp:



2. HOW CAN I READ THE FOLLOWING CHARTS?

Legend:
Information about the dimmability of the lamps. Green means very good dimmability, yellow means limited dimmability, red means undesired dimmability etc.

List of dimmers tested in laboratory conditions

Legend					SUPERSTAR PAR16 35 36*				SUPERSTAR PAR16 50 36*				SUPERSTAR PAR16 80 36*				SUPERSTAR PAR16 80 120*			
Very good dimmability with indicated number of lamps (dimming range greater than 75%)																				
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)					EAN/Basic Code				EAN/Basic Code				EAN/Basic Code				EAN/Basic Code			
Undesired dimmability					405289330153AC0184				40528933017AC0187				405289330218AB41905				405807503688AC03043			
Not relevant					405289330157AC0182				405289330195AC0184				405289330232AB41906				405807503682AC03051			
Not tested					Number of Lamps				Number of Lamps				Number of Lamps				Number of Lamps			
Dimmer					Dimming range		Dimming range		Dimming range		Dimming range		Dimming range		Dimming range		Dimming range			
Brand	Model	Voltage range	Power	Type	1-20	98%-15%	1-13	98%-20%	1-8	97%-23%	1-8	97%-23%	1-20	98%-15%	2-20	97%-12%	2-20	98%-16%	2-20	98%-16%
ABB	STD 50-3	230/50Hz	60-500	L	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%
Altenburger Electronic	50 30	230/50Hz	15-350	T	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%
ALPORA	DSP 400	230/50Hz	400	L	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%	1-10	98%-15%
Berker	2861	230/50Hz	50-420	U	1-20	98%-27%	1-20	98%-26%	1-20	97%-27%	1-20	97%-27%	1-20	98%-27%	1-20	98%-26%	1-20	98%-26%	1-20	98%-26%
Blicino	LNN1441N	230/50Hz			1-15	98%-1%	1-10	97%-5%	1-6	94%-7%	1-6	94%-7%	1-6	98%-1%	2-9	98%-1%	1-6	97%-9%	1-6	97%-9%
Blicino	LNN14408	230/50Hz			2-20	98%-1%	2-9	98%-1%	1-6	97%-9%	1-6	97%-9%	1-6	98%-1%	2-9	98%-1%	1-6	97%-9%	1-6	97%-9%
Blicino	NT4402N	230/50Hz	500	R	3-19	99%-19%	2-12	97%-19%	1-8	95%-22%	1-8	95%-22%	2-20	99%-15%	2-20	98%-17%	2-20	98%-21%	2-20	98%-21%
Busch-Jaeger	6513 U-102	230/50Hz	40-420	T	1-10	96%-22%	1-10	97%-26%	1-10	97%-26%	1-10	97%-26%	1-10	96%-22%	1-10	97%-26%	1-10	97%-26%	1-10	97%-26%
Busch-Jaeger	6523 U-102	230/50Hz	420	T	1-10	96%-22%	1-10	97%-26%	1-10	97%-26%	1-10	97%-26%	1-10	96%-22%	1-10	97%-26%	1-10	97%-26%	1-10	97%-26%
Busch-Jaeger	2250 U	230/50Hz	60-600	L	1-10	98%-1%	2-14	98%-16%	1-9	97%-15%	1-9	97%-15%	1-10	98%-1%	2-14	98%-16%	1-9	97%-15%	1-9	97%-15%
Busch-Jaeger	6526 U	230/50Hz			1-13	98%-34%	1-10	97%-35%	1-5	97%-15%	1-5	97%-15%	1-13	98%-1%	2-14	98%-16%	1-9	97%-15%	1-9	97%-15%
Busch-Jaeger	2247 U-500	230/50Hz			1-20	98%-15%	1-13	98%-20%	1-8	97%-23%	1-8	97%-23%	1-20	98%-15%	1-13	98%-20%	1-8	97%-23%	1-8	97%-23%
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	L	2-13	98%-1%	1-10	98%-5%	1-6	97%-9%	1-6	97%-9%	2-13	98%-1%	1-10	98%-5%	1-6	97%-9%	1-6	97%-9%
DINUY	RE EL1LE1	230/50Hz	400	LED	1-11	98%-1%	1-10	99%-1%	1-5	99%-7%	1-5	99%-7%	1-11	98%-1%	1-10	99%-1%	1-5	99%-7%	1-5	99%-7%
ELKO	400GLI	230/50Hz			1-10	98%-1%	1-10	98%-1%	1-4	97%-1%	1-4	97%-1%	1-10	98%-1%	1-10	98%-1%	1-4	97%-1%	1-4	97%-1%
ELKO	316GLE	230/50Hz	20-315	T	2-20	98%-6%	1-20	98%-7%	1-20	97%-10%	1-20	97%-10%	2-20	98%-6%	1-20	98%-7%	1-20	97%-10%	1-20	97%-10%
ELKO	600GLI	230/50Hz	40-600	U	1-20	98%-1%	1-13	97%-1%	1-8	96%-1%	1-8	96%-1%	1-20	98%-1%	1-13	97%-1%	1-8	96%-1%	1-8	96%-1%
ELKO	420GLEI	230/50Hz	40-420	U	1-14	98%-1%	1-13	97%-4%	1-10	97%-19%	1-10	97%-19%	1-14	98%-1%	1-13	97%-4%	1-10	97%-19%	1-10	97%-19%

Information about the LEDVANCE lamp type

Assessment of the results into categories. Includes the number of lamps and the related dimming range

DIMMER COMPATIBILITY R50+R63+R80

BASISINFORMATIONEN:

1. WAS IST DER PRODUKTCODE UND WO FINDE ICH IHN?

Der Produktcode beschreibt den Lampentyp. Er besteht aus sieben Buchstaben und Ziffern und beginnt mit einem "A". Nachfolgend ein Beispiel eines Produktcodes auf dem Aufdruck der Lampe.



220-240V **AC01770** 2700K
13 W 50/60 Hz 27 mA
Made in Germany XXX-XXXX

2. WIE LESE ICH DIE FOLGENDEN TABELLEN?

Legende: Angaben zur Dimmbarkeit der Lampen. Grün bedeutet eine sehr gute Dimmbarkeit mit der angegebenen Lampenanzahl, gelb bedeutet eine eingeschränkte Dimmbarkeit, rot bedeutet, dass unerwünschtes dimmverhalten auftreten kann etc.









Liste der getesteten Dimmer

Legend					SUPERSTAR							
Very good dimmability with indicated number of lamps (dimming range greater than 75%)					PAR16 35 36*	PAR16 50 36*	PAR16 60 36*	PAR16 80 120*				
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)												
Undesired dimmability					EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code	EAN/ Basic Code				
Not relevant					405283330133/AC01184	405283330171/AC01187	405283330210/AB41305	405807503668/AC03049				
Not tested					405283330157/AC01192	405283330199/AC01194	405283330232/AB41306	405807503632/AC03051				
Dimmer					Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range
ABB	STD 50-3	230V50Hz	60-500	L	1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%
Altenburger Electronic	50 30	230V50Hz	15-350	T	2-20	98% - 15%	2-20	97% - 12%	2-20	98% - 16%	2-20	98% - 16%
AURORA	DSP 400	230V50Hz	400	L	1-10	98% - 15%	2-10	97% - 14%	1-4	96% - 1%	1-4	96% - 1%
Berker	2861	230V50Hz	50-420	U	1-20	98% - 27%	1-20	98% - 25%	1-20	97% - 27%	1-20	97% - 27%
Bicimo	LJNNT441N	230V50Hz			1-15	98% - 1%	1-10	97% - 5%	1-6	94% - 7%	1-6	94% - 7%
Bicimo	LJNNT4408	230V50Hz			2-20	98% - 1%	2-9	98% - 1%	1-6	97% - 3%	1-6	97% - 3%
Bicimo	NT4402N	230V50Hz	500	R	3-18	99% - 19%	2-12	97% - 19%	1-8	95% - 22%	1-8	95% - 22%
Busch-Jaeger	6513 U-102	230V50Hz	40-420	T	2-20	98% - 15%	2-20	98% - 17%	2-20	98% - 21%	2-20	98% - 21%
Busch-Jaeger	6523 U-102	230V50Hz	420	T	1-10	96% - 22%	1-10	97% - 26%				
Busch-Jaeger	2250 U	230V50Hz	60-600	L	1-10		2-14	98% - 16%	1-9	97% - 15%	1-9	97% - 15%
Busch-Jaeger	6526 U	230V50Hz			1-13	98% - 34%	1-10	97% - 35%	1-5		1-5	
Busch-Jaeger	2247 U-500	230V50Hz			1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%
CENTURY CONTROL	MULTI DIMMER	230V50Hz	60-600	L	2-13	98% - 1%	1-10	98% - 5%	1-6	97% - 9%	1-6	97% - 9%
DINJY	RE EL1LE1	230V50Hz	400	LED	1-11	98% - 1%	1-10	98% - 1%	1-5	99% - 7%	1-5	99% - 7%
ELKO	400GLI	230V50Hz			1-10		1-10		1-4	97% - 1%	1-4	97% - 1%
ELKO	316GLE	230V50Hz	20-315	T	2-20	98% - 6%	1-20	98% - 7%	1-20	97% - 10%	1-20	97% - 10%
ELKO	600GLI	230V50Hz	40-600	U	1-20	98% - 1%	1-13	97% - 1%	1-8	96% - 1%	1-8	96% - 1%
ELKO	420GLEI	230V50Hz	40-420	U	1-14	98% - 1%	1-13	97% - 4%	1-10	97% - 19%	1-10	97% - 19%





























Angaben zum LEDVANCE Lampentyp

Bewertung der Testergebnisse in Ampel Kategorien. Beinhaltet sowohl die Lampenanzahl als auch den dimmbaren Bereich








DIMMER COMPATIBILITY R50+R63+R80

Legend					R50 M2 60 36° E14		R50 M2+ 60 36° E14		R63 M2 60 36° E27		R63 M2+ 60 36° E27		R80 M2 60 36° E27		R80 M2+ 60 36°		R80 M2 100 36° E27				
Good dimmability with indicated number of lamps (dimming range greater than 75%)																					
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)																					
Undesired dimmability																					
Not tested																					
					EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code				
					409807562940 / AC5976		409807562940 / AC5976 409807562940 / AC5976		409807562940 / AC5976		409807562940 / AC5976		409807562940 / AC5976		409807562940 / AC5976		409807562940 / AC5976		409807562940 / AC5976		
Dimmer					Dimming range	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
ABB	STD 50-3	230/50Hz	60-500	L	100-19%	89-28%	100-19%	100-19%	100-4%	100-7%	100-4%	100-7%	100-4%	100-7%	100-4%	100-7%	98-2%	98-3%			
Attenburger	50_3	230/50Hz				89-28%	89-28%														
AURORA	DSP 400	230/50Hz	400	L	100-0%	100-0%	100-0%	100-0%	98-0%	100-0%	98-0%	100-0%	98-0%	100-0%	98-0%	100-0%			90-0%		
Beker	2861	230/50Hz	50-420	U		100-11%		100-11%									100-0%	100-0%			
Bicino	LAINT4411 N HCHDHS44 11	230/50Hz			100-0%	100-9%	100-0%	100-9%	92-0%	92-0%	92-0%	92-0%	92-0%	92-0%	92-0%	92-0%	82-0%	86-0%			
Bticino	NT4402N	230/50Hz	500	R																	
Bticino	RW4411				100-0%	100-0	100-0%	100-0													
Bticino	HD4411				100-0%	100-0	100-0%	100-0													
Busch-Jaeger	6513 U-102	230/50Hz	420	T	100-47%	100-47%	100-47%	100-47%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T	100-0%	90-0%	100-0%	90-0%	92-0%	92-0%	92-0%	92-0%	92-0%	92-0%	92-0%	92-0%	100-0%	90-0%			
Busch-Jaeger	2250 U	230/50Hz	60-600	L	98-0%	100-0%	98-0%	100-0%												98-0%	
Busch-Jaeger	6526 U	230/50Hz																			
NTURY CONTI-MULTI DIMMER		230/50Hz	60-600	U	89-0%	90-29%	89-0%	90-29%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	
DimMax	420SL	230/50Hz	200	L/T	93-0%	100-0%	93-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	
DINJY	RE EL1 LE1	230/50Hz	400	LED	100-0%	100-0%	100-0%	100-0%	100-2%	100-1%	100-2%	100-1%	100-2%	100-1%	100-2%	100-1%	100-1%	100-1%	100-0%	100-0%	
DINJY	RE PLALE 1																				
DINJY	RE PLALE 0				100-0%	100-0	100-0%	100-0													
Dominetti	3mMax420 Si	230/50Hz	200	L/T	93-0%	100-0%	93-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	
EcoDIM	EcoDIM 0.3-450W Led Dimmer				100-0%	100-0	100-0%	100-0													
ELKO	400GLI	230/50Hz			91-0%	84-9%	91-9%	84-9%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	90-0%	94-0%			
ELKO	315GLE	230/50Hz	20-315	T	84-0%	92-0%	84-0%	92-0%	92-0%	100-0%	92-0%	100-0%	92-0%	100-0%	92-0%	100-0%					
ELKO	600GLI	230/50Hz	40-600	U	100-11%	100-0%	100-11%	100-0%	94-0%	94-0%	94-0%	94-0%	94-0%	94-0%	94-0%	94-0%	100-0%	100-0%			
ELKO	420GLEA	230/50Hz	40-420	U	84-0%	89-0%	84-0%	89-0%	89-0%	92-0%	89-0%	92-0%	89-0%	92-0%	89-0%	92-0%	82-0%	100-0%			
ELKO	1000LRI	230/50Hz			100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	
ELKO	630GLE	230/50Hz	20-630	U	84-17%	100-13%	84-17%	100-13%												100-0%	
Eltako	UD61NPN-UK	230/50Hz	5-400	R/L/C	93-0%	100-19%	93-9%	100-19%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-10%	
ELTAKO	EUD61NPN-UC				100-0%	100-0	100-0%	100-0												100-0%	
Fetler	40200.LEDxxx	230/50Hz			89-17%	93-11%	89-17%	93-11%												100-0%	
Fetler	40600.RC	230/50Hz			84-17%	100-13%	84-17%	100-13%												100-0%	
Fetler	40600.RL	230/50Hz			100-11%	100-0%	100-11%	100-0%	94-0%	94-0%	94-0%	94-0%	94-0%	94-0%	94-0%	94-0%	100-0%	100-0%			
Fetler	40420.RLC	230/50Hz			84-0%	89-0%	84-0%	89-0%	89-0%	92-0%	89-0%	92-0%	89-0%	92-0%	89-0%	92-0%	82-0%	100-0%			
Fetler	31000	230/50Hz			100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	
FINDER	15.21.8.230.0200				100-0%	100-0	100-0%	100-0													
FINDER	15.21.8.230.8300				100-0%	100-0	100-0%	100-0													
FINDER	15.81.8.230.0500				100-0%	100-0	100-0%	100-0													
FINDER	80.11.0.240.0000																				
Gira	226200	230/50Hz			90-0%	93-0%	90-0%	93-0%	94-0%	100-0%	94-0%	100-0%	94-0%	100-0%	94-0%	100-0%	90-0%	94-0%			
Gira	030700	230/50Hz	20-525	T	92-11%	93-11%	92-11%	93-11%	92-1%	100-0%	92-1%	100-0%	92-1%	100-0%	92-1%	100-0%	100-0%	100-0%			
Gira	117600	230/50Hz	50-420	U	93-0%	100-19%	93-9%	100-19%									100-2%	100-2%			
Gira	217400	230/50Hz	4X20-250	KNX-U	100-19%	100-19%	100-19%	100-19%	100-26%	100-0%	100-26%	100-0%	100-26%	100-0%	100-26%	100-0%	100-23%	100-0%			
Hager	WUD87	230/50Hz	400	LED-U	100-19%	88-17%	100-19%	89-17%	90-0%	92-0%	90-0%	92-0%	90-0%	92-0%	90-0%	92-0%	86-0%	86-0%			
Hamilton	KP1X40	230/50Hz	400		100-0%	100-0%	100-0%	100-0%													
Hugo Müller	adin 8721101	230/50Hz			100-0%	100-0%	100-0%	100-0%	100-2%	100-1%	100-2%	100-1%	100-2%	100-1%	100-2%	100-1%	100-1%	100-1%	100-0%	100-0%	
Ion	Industries LED Dimmer 0.3-350 Watt				100-0%	100-0	100-0%	100-0													
Ion	Industries NEWWWLED Dimmer 600 Watt				100-0%	100-0	100-0%	100-0													
Ion	ID350W-MXII				100-0%	100-0	100-0%	100-0													
Ion	Industries LED Dimmer 200 Watt				100-0%	100-0	100-0%	100-0													
Ion	ID200W-MXII				100-0%	100-0	100-0%	100-0													
Jung	225 N/DE	230/50Hz	20-500	L	90-0%	93-0%	90-0%	93-0%	94-0%	100-0%	94-0%	100-0%	94-0%	100-0%	94-0%	100-0%	90-0%	94-0%			
Jung	225 T/DE	230/50Hz			92-11%	93-11%	92-11%	93-11%	92-1%	100-0%	92-1%	100-0%	92-1%	100-0%	92-1%	100-0%	100-0%	100-0%	100-0%	98-0%	

DIMMER COMPATIBILITY R50+R63+R80

Legend						R50 M2 60 36° E14	R50 M2+ 60 36° E14	R63 M2 60 36° E27	R63 M2+ 60 36° E27	R80 M2 60 36° E27	R80 M2+ 60 36°	R80 M2 100 36° E27	
Good dimmability with indicated number of lamps (dimming range greater than 75%)													
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)													
Undesired dimmability													
Not tested													
						EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	
						405807525940 / AC57976	405807620346 / AC5807 405807620360 / AC5809B	405807626008 / AC45655	405807620308 / AC45641	4058076433328 / AC45656	405807620322 / AC45642	4058076433281 / AC45657	
Dimmer						Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type									
Jung	254 UDIE1	230/50Hz				93-9%	100-19%	93-9%	100-19%				
Jung	1224 LEDUDE	230/50Hz		LED				59-0%	65-0%	59-0%	65-0%		
Jung	3904 REGHE	230/50Hz				100-19%	100-19%	100-19%	100-19%	100-26%	100-0%	100-26%	
JUNG	1731DD					100-0%	100-0	100-0%	100-0				
JUNG	UD 1755 REG					100-0%	100-0	100-0%	100-0				
JUNG	1724 DM					100-0%	100-0	100-0%	100-0				
Legrand	665114	230/50Hz	400	U		100-0%	100-9%	100-0%	100-9%	92-0%	92-0%	92-0%	
Legrand	74319/57433	230/50Hz	400	U		100-0%	100-9%	100-0%	100-9%	92-0%	92-0%	92-0%	
Legrand	72239/57273	230/50Hz	400	U		100-0%	100-9%	100-0%	100-9%	92-0%	92-0%	92-0%	
Legrand	78407/07920	230/50Hz	400	U		100-0%	100-9%	100-0%	100-9%	92-0%	92-0%	92-0%	
Legrand	48869/04887	230/50Hz	400	U		100-0%	100-9%	100-0%	100-9%	92-0%	92-0%	92-0%	
Legrand	067083/84889	230/50Hz	400	U		100-0%	100-9%	100-0%	100-9%	92-0%	92-0%	92-0%	
Legrand	099314	230/50Hz	300	RL								98-0%	
Legrand	770062	230/50Hz	400	RLC		100-9%	100-14%	100-9%	100-14%	100-0%	100-0%	100-0%	
MASTER	DM-DGL	230/50Hz	1000	U/LED						100-42%	100-46%	100-42%	
MASTER	DM-2500	230/50Hz	2500	U/LED		100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	
Merten	IEG5136-000	230/50Hz				84-0%	92-0%	84-0%	92-0%	92-0%	100-0%	100-0%	
Merten	IEG5134-000	230/50Hz				89-17%	93-11%	89-17%	93-11%			100-0%	
Merten	IEG5137-000	230/50Hz				84-17%	100-13%	84-17%	100-13%			100-0%	
Merten	IEG5133-000	230/50Hz				100-11%	100-0%	100-11%	100-0%	94-0%	94-0%	94-0%	
Merten	IEG5138-000	230/50Hz				84-0%	89-0%	84-0%	89-0%	89-0%	92-0%	89-0%	
Merten	IEG 5170-030	230/50Hz	10-200	U						100-0%	100-0%	59-0%	
Merten	MEG 5131	230/50Hz	40-400	L		89-0%	89-0%	89-0%	89-0%	95-0%	93-0%	95-0%	
Merten	MEG 5132	230/50Hz				89-0%	89-0%	89-0%	89-0%	95-0%	93-0%	95-0%	
Merten	MEG 5140	230/50Hz	9-100	L		84-0%	89-0%	84-0%	89-0%	95-0%	95-0%	95-0%	
Merten	MEG 5135	230/50Hz	60-1000	L		100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	
MK	K4501	230/50Hz	180	L			91-0%		91-0%	100-0%	100-0%	100-0%	
NEXUS	881P-01	230/50Hz	400	L						100-0%	97-0%	100-0%	
NIKO	310-0190001901	230/50Hz	5-200	U		100-0%	100-0%	100-0%	100-0%			100-0%	
NIKO	330-0070000701	230/50Hz	5-200	U		100-0%		100-0%		100-0%	100-0%	100-0%	
Odace	S520512	230/50Hz				89-17%	93-11%	89-17%	93-11%			100-0%	
Odace	S520511	230/50Hz				100-11%	100-0%	100-11%	100-0%	94-0%	94-0%	94-0%	
Odace	S520515	230/50Hz				84-0%	89-0%	84-0%	89-0%	89-0%	92-0%	89-0%	
Odace	S520518	230/50Hz				84-0%	89-0%	84-0%	89-0%	95-0%	95-0%	95-0%	
Osram	LED DALI 315 DI	230/50Hz	20-315	DALI-T		100-13%	100-13%	100-13%	100-13%	100-0%	100-0%	100-0%	
PEHA	435 HAN	230/50Hz	60-600	L		89-0%	84-0%	89-0%	84-0%	92-0%	93-0%	92-0%	
Plejd	DIM-01												
Plejd	DIM-02												
Plejd	RTR-01-SW												
RVE	RV LED 250					100-0%	100-0	100-0%	100-0				
Schneider	400GLI	230/50Hz	40-400	T		91-9%	84-9%	91-9%	84-9%	100-0%	100-0%	100-0%	

DIMMER COMPATIBILITY R50+R63+R80

Legend					R50 M2 60 36° E14	R50 M2+ 60 36° E14	R63 M2 60 36° E27	R63 M2+ 60 36° E27	R80 M2 60 36° E27	R80 M2+ 60 36°	R80 M2 100 36° E27	
Good dimmability with indicated number of lamps (dimming range greater than 75%)												
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)												
Undesired dimmability												
Not tested												
					EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	EAN / Basic Code	
					405807592940 / AC57976	4058075620346 / AC58017 4058075620360 / AC58018	4058075926008 / AC45655	4058075620308 / AC45641	405807543328 / AC45656	4058075620322 / AC45642	4058075433281 / AC45657	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type								
Schneider	SBD315RC	230/50Hz			84-0%	92-0%	84-0%	92-0%	92-0%	100-0%	92-0%	100-0%
Schneider	SBD200LED	230/50Hz	400		89-17%	93-11%	89-17%	93-11%			100-0%	100-0%
Schneider	SBD630RC	230/50Hz			84-17%	100-13%	84-17%	100-13%			100-0%	100-0%
Schneider	SBD600RL	230/50Hz			100-11%	100-0%	100-11%	100-0%	94-0%	94-0%	94-0%	94-0%
Schneider	SBD420RCRL	230/50Hz			84-0%	89-0%	84-0%	89-0%	89-0%	92-0%	89-0%	92-0%
Schneider	5170	230/50Hz							100-0%	100-0%	100-0%	59-0%
Schneider	SBD400RL	230/50Hz			89-0%	89-0%	89-0%	89-0%	95-0%	93-0%	95-0%	93-0%
Schneider	SBDSP1	230/50Hz			84-0%	89-0%	84-0%	89-0%	95-0%	95-0%	95-0%	95-0%
Schneider	ATTD1000RL	230/50Hz			100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%	100-0%
Scotmore	MD9014				100-11%	100-10	100-11%	100-10				
Shuttle	JIM-T-LED-500	230/50Hz	2-500	T & LED-T	100-0%	100-5%	100-0%	100-5%	100-0%	100-0%	100-0%	100-0%
Siemens	5TC8 284	230/50Hz	20-525	T	100-20%	100-20%	100-20%	100-20%	98-0%	98-0%	98-0%	98-0%
Siemens	WG1-527-1AB	230/50Hz	20-500	KNX-U	100-19%	100-0%	100-19%	100-0%	100-0%	100-0%	100-0%	100-0%
theben	MAX 544 plus	230/50Hz	250	T	100-0%	100-9%	100-0%	100-9%	100-0%	100-0%	100-0%	100-0%
theben	JIMAX 534 plu	230/50Hz	400	T	100-28%	100-37%	100-28%	100-37%	100-0%	100-0%	100-0%	100-4%
VADSBO	LD 220	230/50Hz	1-200	U					98-20%	100-20%	98-20%	100-20%
VARILIGHT	HQ3W	230/50Hz	400		100-19%	100-5%	100-19%	100-5%	85-0%	85-0%	85-0%	85-0%
VARILIGHT	JQP401W	230/50Hz	400	T	100-0%	100-0%	100-0%	100-0%	100-15%	100-16%	100-15%	100-16%
Varilight	MPI120				100-0%	100-0	100-0%	100-0				
Vimar	20135	230/50Hz	3-100	U	100-19%	100-19%	100-19%	100-19%	100-5%	100-5%	100-5%	100-5%
YOKIS	MTV 500EM				100-0%	100-0	100-0%	100-0				
ZANO	WH401	230/50Hz	400	L	100-0%		100-0%		94-0%	97-0%	94-0%	97-0%
ZANO	WH251	230/50Hz	250		100-0%	100-0%	100-0%	100-0%	95-0%	96-0%	95-0%	96-0%
ZANO	Z GRID 700	230/50Hz	250	LED								
ZANO	Z GRID 500	230/50Hz	500		91-0%	100-0%	91-0%	100-0%	100-0%	100-0%	100-0%	100-0%

Please Note:

- The compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment, and the results can vary in certain field applications due to a number of factors. LEDVANCE does not take over any responsibility, warranty or liability that this results can also achieved by using the devices under other conditions, or when using successor models of the tested devices, or different models of the same manufacturer, or when using other LED lamp types
- The absence of a dimmer from this chart does not necessarily imply incompatibility.
- Please reference the dimmer manufacturer's instructions for installation.
- LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance).
- Subject to change without notice
- Errors and omission excepted
- Always make sure to use the most recent release

Application Notes:

- For best dimming results trailing edge dimmer type is recommended.
- Trailing edge type dimmer requires the neutral wire for installation.

Bitte beachten:

- Die Kompatibilitätsliste basiert auf Tests, die der Hersteller in einer im Labor simulierten Umgebung durchgeführt hat. Die Ergebnisse können aufgrund verschiedener Faktoren in manchen Praxisanwendungen abweichen. LEDVANCE übernimmt keinerlei Verantwortung, Garantie oder Haftung dafür, dass diese Ergebnisse tatsächlich mit den Geräten unter anderen Bedingungen, mit Nachfolgemodellen der getesteten Geräte, mit anderen Modellen desselben Herstellers oder bei Verwendung anderer LED-Lampentypen erreicht werden.
- Das Fehlen eines Dimmers in der Abbildung bedeutet nicht, dass ein Dimmer nicht kompatibel ist.
- Lesen Sie stets die Installationsanweisungen des Dimmerherstellers.
- LED-Lampen bestehen aus mehreren elektronischen Komponenten. Unter ungünstigen Bedingungen können diese Störgeräusche erzeugen. Im Resonanzfall können selbst geringe Geräusche einen hörbaren Effekt hervorrufen. Einflussfaktoren können die Installation, die Gestaltung des Lampenträgers, die Leuchte (akustischer Resonanzeffekt), der Dimmer oder der Trafo (Oberschwingungen oder elektronische Resonanz) sein.
- Änderungen vorbehalten.
- Irrtümer und Auslassungen vorbehalten.
- Vergewissern Sie sich, dass Sie stets die aktuellste Version benutzen.

Anwendungshinweis:

- Um bestmögliche Dimmergebnisse zu erzielen, wird die Verwendung von Phasenabschnitt-Dimmern empfohlen.
- Phasenabschnitt-Dimmer erfordern bei der Installation einen Neutralleiter.

LEDVANCE GmbH

Head Office:

Parkring 1-5
85748 Garching, Germany
Phone +49 89 780673-100
Fax +49 89 780673-XXX
www.ledvance.com