

LEDVANCE

# PRECISION MEETS POWER

## OPTI-SELECT FLOODLIGHT

PERFORMANCE  
CLASS

### SIMPLIFYING YOUR WORK

- OPTI-SELECT: Narrow, medium and wide beam angles in the same product, easily adjustable in the field via switch.
- FLEX MOUNT: Two mounting options already inside the box (knuckle and trunnion mount or slipfitter and trunnion mount).
- Wattage and CCT selectable for maximum versatility.



OPTISELECT



FLEXMOUNT



# LEDVANCE


## ORDERING GUIDE

FLOODLT	P	SXXX	XXX	D	8	SC2	ADX	BZ	P
PRODUCT NAME	SEGMENTATION	WATTAGE	VOLTAGE	DIMMING	CRI	COLOR TEMPERATURE	BEAM ANGLE	COLOR/FINISH	OPTIONS
FLOODLT = Floodlight	P = Performance Class	S030 = 15/25/30W S060 = 35/45/60W S140 = 80/100/140W S300 = 200/250/300W S470 = 350/400/470W	UNH = 120-347V HUV = 277-480V	D = 0-10V Dimming	8 = >80 CRI	SC2 = 3000/4000/5000K	ADJ = 55/75/90° ADN = 25/30/35°	BZ = Bronze	P = Photocell

## FEATURES

### OPTISELECT

Beam angle adjustable via switch, no lens swap needed.



### WATTAGE/CCT SELECTABLE

Aids in inventory reduction & greater job site flexibility.

### FLEXMOUNT

Two mounting options inside the box for ease of installation (1/2" NPS knuckle + trunnion or slip fitter + trunnion). Yoke mount available as accessory.



### INTEGRATED PHOTOCELL (30/60/140W)

Can be disabled via On/Off switch

### 3-PIN NEMA RECEPTACLE (300W/470W)

with shorting cap (optional Photocell).



## ACCESSORIES



WALL BRACKETS



TENON ADAPTER FOR LOW WATTAGE FLOODLIGHTS



YOKE MOUNTS

LEDVANCE LLC  
181 Ballardvale Street, Suite 203  
Wilmington, MA 01887 USA  
Phone: 1-800-LIGHTBULB (1-800-544-4828)  
www.ledvanceUS.com

LEDVANCE is a registered trademark.  
All other trademarks are those of their respective owners.  
Specifications subject to change without notice.



SCAN TO FOLLOW US  
ON SOCIAL MEDIA



Spec Sheet



Install Guide