

POWERED THROUGH SUSTAINABLE INNOVATION





DAMP PROOF HIGH EFFICIENCY



PERFOR-MANCE CLASS

ONE RANGE, MANY OPTIONS

SUSTAINABLE LIGHTING FOR MODERN INDUSTRIAL ENVIRONMENTS

Efficiency meets longevity: the DAMP PROOF HIGH EFFICIENCY range featuring classic shapes offers reliable and energy-efficient lighting for industrial and technical areas – and is particularly suited for industrial facilities with low to mid-height ceilings and environments without high humidity exposure.

With a luminous efficacy of up to 164 lm/W, a lifetime of 100 000 hours (L80) and IP65/IK08 protection, the luminaires are ideal for long-term use in demanding conditions. Their tool-free installation and choice of versions make them fit for a wide range of applications, including car parks, workshops, underpasses, storage areas and assembly lines.

Both light source and driver are easy to upgrade thanks to EVERLOOP. Combined with the MULTI LUMEN function, this range can be adapted to a variety of projects while reducing the need for maintenance and complete lighting system replacements.




With EVERLOOP, the DAMP PROOF HIGH EFFICIENCY luminaire offers a sustainable alternative to full replacements. Thanks to its modular design, both driver and light source can be easily upgraded – without the need to replace the entire luminaire. This makes maintenance simpler, more cost-effective, and environmentally friendlier.

For details, see the user instructions and our how-to video







Easy light source replacement



MULTI LUMEN FUNCTION: power step selectable on site

HIGH LIFETIME: up to 100 000 h (L80) to minimise maintenance

HIGH EFFICIENCY: up to 164 lm/W for reduced energy consumption

FLEXIBLE OPTIONS: On/off,
DALI and through-wiring versions

QUICK INSTALLATION: thanks to tool-free electrical connection




WOULD YOU LIKE MORE INFORMATION?

Visit our website to discover more technical details on the product range ledvance.com/DP-HE



Does your project require something not shown? LEDVANCE Project Services can create lighting solutions to fit your specific needs. Get in touch: contact@ledvance.com





DIP switch for easy power steps setting.

ADJUST AND GOPOWERED BY MULTI LUMEN

Thanks to the MULTI LUMEN feature, you can adjust the luminous flux in several steps to match on-site requirements – for optimal lighting across a wide range of applications. This flexibility simplifies project planning and supports your daily business.

Please refer to the user instructions for detailed settings. Learn more at **ledvance.com/multiselect**

DAMP PROOF HIGH EFFICIENCY	Max.	Lumen	Min.
1200 29 W On/Off & Throughwiring	4640	5 settings	2260
1500 40 W On/Off & Throughwiring	6 400	7 settings	2590
1500 73 W On/Off & Throughwiring	11 680	4 settings	7780

Subject to change without notice. Errors and omission excepted.

LEDVANCE EU-W MK TRA

With business activities in over 140 countries, LEDVANCE is one of the world's leading general lighting companies. Emerging from OSRAM's general lighting division, LEDVANCE's portfolio includes LED lamps and luminaires, intelligent lighting products, traditional lamps and renewable energy solutions.

#POWERTHROUGHLIGHT



LEDVANCE GmbH Parkring 1-5 85748 Garching Germany

DAMP PROOF HIGH EFFICIENCY





Product name	EAN (GTIN)	Replacment for	w	lm	lm/w	K	L80 ¹			L×W×H [mm] Ø×H [mm]
DAMP PROOF HIGH EFFICIENCY – Ro	bust damp-proof lur	ninaires with ver	ry hiah efficiency			D		LICKER MALUE :5%	CRI >80	65 IK 08 5 VEAGG
DP HE 1200 P 29W ML 840 IP65	4099854 406751	2×36W FL	28.3/24/21.4/17.3/14	4640/3900/3460/2810/2260	164/163/162/161	4000	100000	120	_	1200 × 82 × 68
DP HE 1500 P 40W ML 840 IP65	4099854 406799	2×58W FL	39.3/35/31.1/26.9/23.4/20/16	6400/5700/5070/4360/3810/3240/2590	163/162	4000	100000	120	-	1500 × 82 × 68
DP HE 1500 P 73W ML 840 IP65	4099854 406836	2×80W FL	72.2/63.3/55.2/47.6	11680/10300/9010/7780	162/163	4000	100000	120	-	1500 × 82 × 68
DAMP PROOF HIGH EFFICIENCY DAL	I – Robust damp-pro 4099854 406874	of luminaires wi	th very high efficiency and DALI-2	technology 4640	160	4000	100000	120	CRI >80 IP 6 DALI-2	GUARANTEE
DP HE DA 1500 P 23W 840 IP65	4099854 406911	1 × 58 W FL	23	3680	160	4000	100000	120	DALI-2	1500 × 82 × 68
DP HE DA 1500 P 40W 840 IP65	4099854 406959	2×58W FL	40	6400	160	4000	100000	120	DALI-2	1500 × 82 × 68
DP HE DA 1500 P 49W 840 IP65	4099854 406997	2×70W FL	49	7800	160	4000	100000	120	DALI-2	1500 × 82 × 68
DAMP PROOF HE 5X THROUGHWIRIN	IG – Robust damp-pr	oof luminaires w	vith very high efficiency and 5×2.	5 mm² throughwiring		D		LICKER MALUE :5%	CRI >80	65 IK08 5 YEARS GUMANTEE
DP HE 5TH 1200 P 29W ML 840 IP65	4099854 480621	2×36W FL	28.3/24/21.4/17.3/14	4640/3900/3460/2810/2260	164/163/162/161	4000	100000	120	-	1200 × 82 × 68
DP HE 5TH 1500 P 40W ML 840 IP65	4099854 407031	2×58W FL	39.3/35/31.1/26.9/23.4/20/16	6400/5700/5070/4360/3810/3240/2590	163/162	4000	100000	120	-	1500 × 82 × 68
DP HE 5TH 1500 P 73W MI 840 IP65	4099854 480669	2 × 80 W FI	72.2/63.3/55.2/47.6	11680/10300/9010/7780	162/163	4000	100000	120	_	1500 × 82 × 68

¹t[h]: L70/B50 @ 25 °C (T₂), t[h]: L80/B10 @ 25 °C (T₂), t[h]: L90/B10 @ 25 °C (T₂) | ²Refer to www.ledvance.com/guarantee for precise conditions Safety Notice: Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.