

LEDVANCE

MODERN AND CONTEMPORARY FLUSH MOUNT PANEL

VALUE
CLASS

SIMPLIFYING YOUR WORK

- DUAL SELECTABILITY: Three CCTs and three wattage outputs in the same luminaire.
- Each panel includes all mounting hardware including mounting plate, wall anchor screws, wire connectors, and retaining screws
- Panels feature a universal voltage range of 120-347V, along with 0-10V dimming





LEDVANCE

ORDERING GUIDE

PANELF	V	0XX	UNH	D	8	SC2	XX	FM	WH	G1
PRODUCT NAME	SEGMENTATION	WATTAGE	VOLTAGE	DIMMING	CRI	COLOR TEMP	DIMENSIONS	MOUNTING METHODS	FINISH	GENERATION
PANELF = LED Flat Panel	V = Value Class	040 = 20/30/40W 055 = 36/45/55W	UNH = 120-347V	D = 0-10V Dimming	8 = >80	SC2 = 3000, 4100, or 5000K	14 = 1' x 4' 22 = 2' x 2' 24 = 2' x 4'	FM = Flush Mount	WH = White	G1 = Generation 1

FEATURES

DUAL SELECTABILITY

CCT and Wattage selectable located via switches on the driver.
~2' cable lead for wire mgmt.

INSTALLATION

Installs directly on a junction box via the aid of the mounting plate.

MODERN DESIGN

Back Lit Panel, Low Profile Design.

SUPERIOR CONSTRUCTION

Cold-Rolled Steel Back, Aluminum Frame.

ASSORTED SIZES

Comes in a 1X4, 2X2 or 2X4 option and just 1.4" in depth.

VERSATILITY

Additional mounting option available.
Suspended mounting (Part number says: Pendant Mount Kit sold separately).

ACCESSORIES

PENDANT MOUNT KIT FOR
FLUSH MOUNT PANELS
66373



WIRE COVER PLATE
AND HOOKS –
INCLUDED WITH PANEL



MOUNTING PLATE
AND HARDWARE



LEDVANCE LLC
181 Ballardvale Street, Suite 203
Wilmington, MA 01887 USA
Phone: 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

LEDVANCE is a registered trademark.
All other trademarks are those of their respective owners.
Specifications subject to change without notice.



SCAN TO FOLLOW US
ON SOCIAL MEDIA



Spec Sheet



Install Guide