

CERTIFICATE

No. U6 097386 0678 Rev. 00

Holder of Certificate: **LEDVANCE GmbH**

Parkring 1-5
85748 Garching
GERMANY

Certification Mark:




Product: **Luminaires for emergency lighting
(LED Fixed luminaires)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142255001701

Date, 2025-05-28



(Taylor Yao)

CERTIFICATE

No. U6 097386 0678 Rev. 00

Model(s):

HB FLEX P 240W 35 ML 840 WT;
HB FLEX P 240W 70 ML 840 WT;
HB FLEX P 240W 110 ML 840 WT;
HB FLEX P 240W 35x80 ML 840 WT;
HB FLEX P 240W 35 ML 865 WT;
HB FLEX P 240W 70 ML 865 WT;
HB FLEX P 240W 110 ML 865 WT;
HB FLEX P 240W 35x80 ML 865 WT;
HB FLEX DA P 240W 35 840 WT;
HB FLEX DA P 240W 70 840 WT;
HB FLEX DA P 240W 110 840 WT;
HB FLEX DA P 240W 35x80 840 WT;
HB FLEX DA P 240W 35 865 WT;
HB FLEX DA P 240W 70 865 WT;
HB FLEX DA P 240W 110 865 WT;
HB FLEX DA P 240W 35x80 865 WT

Brand Name:

LEDVANCE

**Parameters:**

Rated Voltage: 220-240VAC/DC
Rated Frequency: 0/50/60Hz
Rated Power: See below table for details
Protection Class: I
Degree of Protection: IP66
Blue Light Risk Group: RG1
ta: 50°C



Product Service

CERTIFICATE

No. U6 097386 0678 Rev. 00

Model No.	Rated Power (W)
HB FLEX P 240W 35 ML 840 WT; HB FLEX P 240W 70 ML 840 WT; HB FLEX P 240W 110 ML 840 WT; HB FLEX P 240W 35x80 ML 840 WT; HB FLEX P 240W 35 ML 865 WT; HB FLEX P 240W 70 ML 865 WT; HB FLEX P 240W 110 ML 865 WT; HB FLEX P 240W 35x80 ML 865 WT	120/180/240
HB FLEX DA P 240W 35 840 WT; HB FLEX DA P 240W 70 840 WT; HB FLEX DA P 240W 110 840 WT; HB FLEX DA P 240W 35x80 840 WT; HB FLEX DA P 240W 35 865 WT; HB FLEX DA P 240W 70 865 WT; HB FLEX DA P 240W 110 865 WT; HB FLEX DA P 240W 35x80 865 WT	240

**Tested
according to:**

EN IEC 60598-2-22:2022
EN 60598-2-24:2013
EN IEC 60598-2-1:2021
EN IEC 60598-1:2021/A11:2022

**Production
Facility(ies):**

097968