

PRODUCT DATASHEET

SL FLEX LA RV25ST P 158W 730 WAL

STREETLIGHT FLEX LARGE RV25ST | Light distribution for general road lighting



Areas of application

- Outdoor use (IP66)
- M-, C- and P-class roads acc. to EN 13201
- Parking
- Public areas
- Industry

Product benefits

- Durable design and highest quality component selection for long lasting performance
- Quick and easy wiring, due to tool-free housing opening and push button terminal
- High light uniformity
- 3 light colors available, perfectly suited to illuminate highly diverse surroundings
- No upper light output ratio (ULOR 0%) when mounted at 0° tilt
- Automatic mains disconnection when opening the housing
- 5 years guarantee

Product features

- Light distributions optimized for streets of similar width to the pole height
- Very long lifetime (L90/B10): Up to 100,000 h (at 25 °C)
- Spigot for 48-60 mm poles included
- Additional reduction for 42 mm and adapter for 76 mm poles available separately
- Adjustable spigot for both side-entry and post-top installation
- +/- 15° tilt angle adjustment without opening the housing



- High luminous efficacy: up to 155 lm/W
- Operating temperature: -40...50 °C
- High surge protection: up to 10 kV (L/N-GND)
- Provides functional or mood lighting
- Protection class: II


TECHNICAL DATA

Electrical data

| | |
|---|-----------------------|
| Nominal wattage | 158.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 756 mA |
| Inrush current | 80 A |
| Inrush current time T_{h50} | 150 μ s |
| Max. number of luminaires per miniature circuit breaker B16 | 7 |
| Max. number of luminaires per miniature circuit breaker C10 | 8 |
| Max. number of luminaires per miniature circuit breaker C16 | 14 |
| Power factor λ | > 0.90 |
| Total harmonic distortion | < 10 % |
| Protection class | II |
| Operating mode | Integrated LED driver |

Photometrical data

| | |
|--|----------------------|
| Luminous flux | 23350 lm |
| Luminous efficacy | 148 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | 70 |
| Standard deviation of color matching | < 5 sdc _m |
| Low flicker | Yes |
| Photobiological safety group acc. to EN62778 | RG1 |
| Photobiological safety group acc. to EN62471 | RG1 |
| Beam angle | 25 ° x 145 ° |



SL FLEX LA P 158W 730 RV25ST
WAL

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 617.00 mm |
| Width | 300.00 mm |
| Height | 90.00 mm |
| Product weight | 7700.00 g |

SL FLEX LA P RV WAL

Materials & Colors

| | |
|--|----------------|
| Product color | White aluminum |
| Housing color | White aluminum |
| Body material | Aluminum |
| Cover material | Tempered glass |
| Light emitting surface material | Glass |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|------------------------------|--------------------|
| Ambient temperature range | -40...+50 °C |
| Temperature range at storage | -30...+80 °C |
| Type of connection | Screwless terminal |
| Type of protection | IP66 |

| | |
|--|----------|
| Protection class IK (shock resistance) | IK08 |
| Dimmable | No |
| Mounting type | Post top |
| Mounting location | Pole |
| Application environment | Outdoor |
| Adjustable | Yes |
| With light source | Yes |

Lifespan

| | |
|----------------------------|------------------------|
| Lifespan L70/B50 at 25 °C | 100000 h ¹⁾ |
| Lifespan L80/B10 at 25 °C | 100000 h ¹⁾ |
| Lifespan L80/B50 at 25 °C | 100000 h |
| Lifespan L90/B10 at 25 °C | 100000 h |
| Number of switching cycles | 100000 |

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)



Control gear

| | |
|-----------------------------|--------|
| Output current | 625 mA |
| ECG - Output ripple current | ≤ 10 % |

Certificates & Standards

| | |
|--|-----------------------|
| Standards | CE / ENEC / EAC / EPD |
| Luminaire with limited surface temperature, "D sign" | No |
| Ball shot safe | No |
| EPD | LEDV-00023-V01.01-EN |
| Replaceable light source (EPREL) | Not replaceable |















Accessories Optional


| Product image | Product name | EAN |
|---|----------------------------------|---------------|
|  | SL FLEX SPIGOT 76MM WAL | 4058075552531 |
|  | SL FLEX REDUCTION 60 TO 42MM WAL | 4058075552579 |

EQUIPMENT / ACCESSORIES

– Spigot for 42 and 76 mm poles available separately

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|------------------------------------|
|  | User instruction / safety instructions | SL FLEX WAL |
|  | Legal information | LSI SL FLEX LA P |
|  | Legal information | Legal insert SL FLEX WAL |
|  | Legal information | Informationstext 18 Abs 4 ElektroG |
|  | Legal information | Safety Insert G11218810 |
|  | Declarations of conformity | SL FLEX MD |
|  | Declarations of conformity UKCA | SL FLEX WAL |
| Photometric and lighting design files | | Document name |
|  | IES file (IES) | SL FLEX LA P 158W 730 RV25ST WAL |
|  | LDT file (Eulumdat) | SL FLEX LA P 158W 730 RV25ST WAL |
|  | ULD file (DIALux) | SL FLEX LA P 158W 730 |
|  | ROLF file (RELUX) | SL FLEX LA P 158W 730 |
|  | Light distribution curve type polar | SL FLEX LA P 158W 730 RV25ST WAL |
| CAD/BIM files | | Document name |
|  | BIM Revit 3D | SL FLEX LA |
|  | CAD STEP 3D | SL_FLEX_LA |

| Tender texts | Document name |
|---|---|
|  Tender documents | STREETLIGHT FLEX LARGE RV25ST P 158W 730 WAL-EN |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075552494 | Shipping box 1 | 678 mm x 378 mm x 227 mm | 8735.00 g | 58.18 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.