

PRODUCT DATASHEET

SUN@Home Downlight Slim 225mm

Sun@Home Downlights | Downlight with Human Centric Lighting Technology

Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



Product benefits

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and –intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation

Product features

- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum



- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature

TECHNICAL DATA

Electrical data

| | |
|---|---------------|
| Nominal wattage | 22.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 150.000 mA |
| Inrush current | 30 A |
| Max. number of luminaires per miniature circuit breaker B16 | 5 |
| Max. number of luminaires per miniature circuit breaker C10 | 5 |
| Max. number of luminaires per miniature circuit breaker C16 | 8 |
| Power factor λ | > 0.70 |
| Protection class | II |
| Operating mode | Mains voltage |

Photometrical data

| | |
|--|---------------|
| Luminous flux | 1500 lm |
| Total luminous flux of contained light sources | 1950 lm |
| Luminous efficacy | 75 lm/W |
| Color temperature | 2200...5000 K |
| Reference control setting of contained light source (Kelvin) | 2700 K |
| Light color (designation) | Tunable White |
| Color rendering index Ra | > 95 |
| Standard deviation of color matching | ≤6 sdcn |
| Flickering metric (Pst LM) | ≤ 1 % |
| Photobiological safety group acc. to EN62778 | RG0 |
| Photobiological safety group acc. to EN62471 | RG0 |
| Beam angle | 110 ° |

Dimensions & Weight

| | |
|----------------|-----------|
| Diameter | 225.00 mm |
| Height | 33.50 mm |
| Product weight | 273.00 g |

HCL SMART Downlight 225 TW

Materials & Colors

| | |
|-----------------|------------------|
| Product color | White |
| Housing color | White |
| Body material | Plastic |
| Cover material | Polystyrene (PS) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|------------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+60 °C |
| Type of connection | Terminal |
| Type of protection | IP20 |
| Dimmable | Yes |
| Type of dimming | WiFi |
| Mounting type | Recessed |
| Mounting location | Ceiling |
| Application environment | Indoor |
| Mounting diameter | 200 mm |
| With light source | Yes |

Lifespan

| | |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C | 25000 h |
| Number of switching cycles | 15000 |

Emergency lighting

| | |
|--|---|
| Luminous flux in maintained operation mode | - |
|--|---|

Certificates & Standards






| | |
|--|-----------------|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |
| Replaceable light source (EPREL) | Not replaceable |

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.

– Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|---|
|  | User instruction / safety instructions | SUN@HOME DOWNLIGHT SLIM |
|  | Legal information | SUN@HOME |
|  | Declarations of conformity | SUN@HOME Downlight Slim |
|  | Declarations of conformity UKCA | SMART WIFI AND SUNATHOME DOWNLIGHT SLIM |
| CAD/BIM files | | Document name |
|  | BIM Step 3D | Sun@Home DL Slim 225 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075575851 | Folding box 1 | 42 mm x 234 mm x 238 mm | 358.00 g | 2.34 dm ³ |
| 4058075575868 | Shipping box 6 | 262 mm x 240 mm x 247 mm | 2330.00 g | 15.53 dm ³ |
| 4058075657106 | Shipping box 24 | 544 mm x 500 mm x 272 mm | 10626.00 g | 73.98 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.