

# PRODUCT DATASHEET

## SMART+ Wifi Undercabinet Slim 50x3.75 TW

SMART+ UNDERCABINET SLIM TUNABLE WHITE | Slim Undercabinet luminaire with WIFI technology



### Areas of application

- Indoor applications
- Shelf and undercabinet lighting
- Kitchens, workspaces
- Shelves

### Product benefits

- Wireless control via app or voice control
- Very slim design
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

### Product features

- Variety of combinations possible
- Provides functional or mood lighting
- Adjustable color temperature via Tunable White: 2,700...6,500 K
- Dimmable
- Available in different sizes: 50x3.75 cm, 45.7x6.5 cm, 60x6.5 cm
- 50 cm luminaire extendable with maximum two extensions of 50 cm each
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Network protocol: WiFi
- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0)



## TECHNICAL DATA

### Electrical data

Nominal wattage	9.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	58.000 mA
Inrush current	38 A
Max. number of luminaires per miniature circuit breaker B16	137
Max. number of luminaires per miniature circuit breaker C10	86
Max. number of luminaires per miniature circuit breaker C16	137
Power factor $\lambda$	$\geq 0.5$
Protection class	II
Operating mode	Integrated LED driver

### Photometrical data

Luminous flux	480 lm
Total luminous flux of contained light sources	900 lm
Luminous efficacy	53 lm/W
Color temperature	2700...6500 K
Reference control setting of contained light source (Kelvin)	2700 K <sup>1)</sup>
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	120 °

1) Performing a reset will restore the default values set by the manufacturer

### Dimensions & Weight

Length	500.00 mm
Width	38.00 mm
Height	8.00 mm
Product weight	350.00 g
Cable length	1500 mm

SMART WIFI UNDERCABINET

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum Plastic
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Cabinet undersides
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Emergency lighting

Luminous flux in maintained operation mode	-
--	---

Certificates & Standards

Standards	CE
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable





EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- Power supply (2 m) and control box (5 cm) is included with basic version
- Extensions available in lengths: 30 cm and 50 cm
- Extensions are supplied with a connector and a connector cable (10 cm)
- Power supply and control box are not included with extensions
- For control via SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

### Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	SMART WIFI UNDERCABINET
	Legal information	Legal Insert SUNATHOME AND SMART WIFI
	Declarations of conformity	SMART WIFI UNDERCABINET TW
	EU Data Act	SMART WiFi Lamps and Luminaires

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075576278	Folding box 1	78 mm x 60 mm x 514 mm	512.00 g	2.41 dm <sup>3</sup>
4058075576285	Shipping box 8	542 mm x 342 mm x 150 mm	4771.00 g	27.80 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

- Further information and frequently asked questions (FAQs) at [www.ledvance.com/consumer/smart/faq](http://www.ledvance.com/consumer/smart/faq)

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

