

PRODUCT DATASHEET DP 1200 TH-KIT 5x2.5

DAMP PROOF ACCESSORIES | Throughwiring kits for DP GEN 2



Product benefits

- Easy installation and tool-free electrical connection


Product features

- Through-wiring kits with tool-free connectors

TECHNICAL DATA

Dimensions & Weight

| Length | 1045 mm |
|----------------|----------|
| Width | 50 mm |
| Product weight | 220.00 g |



DP 1200 TH-KIT 5x2.5

Materials & Colors

| Product color | Multicolored |
|--------------------------|--------------|
| Application & Mounting | |
| Replaceable light source | No |
| Certificates & Standards | |
| Standards | CE |
| | |

EQUIPMENT / ACCESSORIES

- 5x2.5 mm 2 cables with tool-free connector incl. EMI filter and cable gland inserts for 10-14 mm cables

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|--|------------------------------------|
| PDF | User instruction / safety instructions | UI Damp Proof IP65 |
| PDF | Legal information | Informationstext 18 Abs 4 ElektroG |
| PDF | Declarations of conformity | CE Declaration Damp Proof |

| | Documents and certificates Document name | |
|-----|--|---------------------------|
| POF | Declarations of conformity | CE Declaration Damp Proof |
| PDF | Declarations of conformity UKCA | DP 1200 TH-KIT 5x2.5 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075695030 | BAG 1 | | 222.00 g | |
| 4058075695047 | Shipping box 30 | 555 mm x 320 mm x 325 mm | 7537.00 g | 57.72 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.