

# PRODUCT DATASHEET LED Performance HighBay 1-10V 200 W/6500 K

LED PERFORMANCE HIGHBAY 1-10V | High-bay luminaires



# Areas of application

- Industrial and commercial halls
- Warehouses
- Public areas (stations, stadiums)
- Airports

# Product benefits

- Pre-wired with 500 mm flying cable
- Low maintenance costs thanks to long lifetime

#### **Product features**

- Die-casting aluminum offer a heavy-duty housing and high efficacy heat-dissipation
- High system efficiency up to 140 lm/W
- Available with wattage: 90 W, 120 W, 150 W, 200 W
- Available with color temperature: 4,000 K, 6,500 K
- Color rendering index  $R_a$ : > 80
- Power factor: > 0.9
- 1-10V dimming driver
- Type of protection: IP65
- Impact resistance: IK08
- Certificate: CB

# **TECHNICAL DATA**

# Electrical data

Nominal wattage	200.00 W	
Nominal voltage	100277 V	
Mains frequency	5060 Hz	
Power factor $\lambda$	> 0.90	
Total harmonic distortion	< 20 %	
Protection class	1	

# Photometrical data

Luminous flux	28000 lm
Luminous efficacy	140 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Standard deviation of color matching	< 5 sdcm

# Dimensions & Weight

Diameter	321.00 mm
Height	120.80 mm
Product weight	2650.00 g
Cable length	500 mm

LDPFM HB 1-10V 200W 277V

# Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-30+50 °C	
Temperature range at storage	-40+70 °C	
Type of connection	Cable, 3-pole	
Type of protection	IP65	
Protection class IK (shock resistance)	IK08	

Dimmable	Yes
Type of dimming	1-10V
Mounting location	Ceiling
Application environment	Indoor
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	50000 h <sup>1)</sup>
Number of switching cycles	50000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

#### Certificates & Standards

Standards CB / EMC / RoHS	Standards
---------------------------	-----------

# DOWNLOAD DATA

Photometric and lighting design files	Document name	
IES file (IES)	LDPFM HB 1-10V 200W 865	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075420656	Shipping box	377 mm x 377 mm x 162 mm	3157.00 g	23.02 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.