

PRODUCT DATASHEET OTi DALI 35/220...240/400 D LT2 L

OPTOTRONIC© Intelligent - Dimmable DALI (non-isolated) | Constant Current - Indoor



Areas of application

- Linear lighting for office, education, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for luminaires of protection class I

Product benefits

- Fully programmable via software (DALI Interface)
- Flexible current setting (LEDset2)
- Lifetime: up to 100,000 h (temperature at $T_c = 65$ °C, max. 10 % failure rate)
- High-quality dimming of 1...100 % by amplitude dimming (except 80 W versions)
- High quality of light thanks to <1% output ripple current
- Very high efficiency
- $-\,$ Very low standby power consumption: < 0.15 W *
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

Versatile scope of application due to OSRAM DALI Technology:

- Easy to use in corridors and restrooms because of three-level Corridor function
- Touch DIM application: easy to control via pushbutton or sensor
- Energy efficient Touch DIM operation due to automatic switch-off at sufficient residual light
- Suitable for emergency Installations (acc. to EN 60598-2-22 and IEC 61347-2-13, appendix J) thanks to DC detection (0 Hz, pulsating DC), on/off switchable
- Feedback of power consumption and operating hours (Fit for SMART GRID)
- Suitable for buildings according to EPBD/BREEAM/LEED due to automatic Constant Lumen Output setting
- Luminaire information for easy maintenance

Product features

- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Versatile DALI window driver up to 80 W due to flexible output characteristic
- Supply voltage: 220...240 V
- Available with output current range: up to 2,100 mA
- Constant Lumen Output (CLO)
- Integrated customizable thermal management (Driver Guard)
- DALI-2 certified (Part -101,-102 and -207)

TECHNICAL DATA

Electrical data

Nominal wattage	35.00 W
Nominal output power	438 W
Nominal voltage	220240 V
Nominal output voltage	54240 V ¹⁾
Input voltage AC	198264 V ²⁾
Input voltage DC	176276 V
U-OUT (working voltage)	< 250 V
Nominal current	0.19 A
Nominal output current	75400 mA ³⁾
Inrush current	17 A ⁴⁾
Output current tolerance	±3 % ⁵⁾
Output ripple current (100 Hz)	< 1 %
Mains frequency	0/50/60 Hz
Total harmonic distortion	< 10 %
Power factor λ	> 0.95 ⁶⁾
ECG efficiency	≤92 % ⁷⁾
Device power loss	4 W ⁸⁾
Max. ECG no. on circuit breaker 10 A (B)	18
Max. ECG no. on circuit breaker 16 A (B)	28
Max. ECG no. on circuit breaker 25 A (B)	43
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	Non isolated
Power loss in stand-by mode	< 0.25 W
Flickering metric (Pst LM)	≤1

¹⁾ Maximum 350 V

Photometrical data

Flickering metric (Pst LM)	≤1
----------------------------	----

²⁾ Permitted voltage range

³⁾ $_{\pm5\%}$

⁴⁾ At 170 µs

⁵⁾ When use DALI

⁶⁾ Full load at 230 V

⁷⁾ At full load and 230 V

^{8) &}lt;sub>Maximum</sub>

Stroboscope effect metric (SVM)	≤0.4
---------------------------------	------

Dimensions & Weight



Length	280.00 mm
Mounting hole spacing, length	270,0 mm
Width	30.00 mm
Height	21.00 mm
Cable cross-section, input side	0.51.5 mm ² 1)
Cable cross-section, output side	0.51.5 mm ² 1)
Wire preparation length, input side	8.59.5 mm
Wire preparation length, output side	8.59.5 mm
Product weight	205.00 g

¹⁾ Solid or flexible leads

Colors & materials

Product color	White
Casing material	Metal
Body material	Metal

Temperatures & operating conditions

Ambient temperature range	-25+60 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	50000 h / 100000 h ¹⁾
--------------	----------------------------------

¹⁾ At maximum T_{c} = 75°C / 10% failure rate / At T_{c} = 65 °C / 10 % failure rate

Additional product data

Ī	Encapsulated	No
	· ·	

Capabilities

Dimmable	Yes
Dimming interface	DALI-2 / Touch DIM / Touch DIM Sensor
Dimming range	1100 % 1)
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	I
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

¹⁾ For maximum nominal output current

Certificates & Standards

Approval marks – approval	CE / EL / ENEC 10 / VDE-EMC / CCC / RCM
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384 / Acc. to EN 62386
Protection class	I
Type of protection	IP20

LOGISTICAL DATA

|--|

Energy labelling regulation data acc EU 2019/2015

Networked standby power for CLS	≤0.30 W
---------------------------------	---------

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	OPTOTRONIC® LED Power Supply
PDF	Declarations of conformity	INOTEC- Conformity declaration AM00139_OTiDALI35_220_240_400_D_LT2_L
PDF	Declarations of conformity	EATON(CEAG)-Conformity declaration AN00948 OTI DALI 35/220-240/400 D LT2 L
PDF	Declarations of conformity	INOTEC-Conformity declaration AN00948 OTI DALI 35/220-240/400 D LT2 L
PDF	Declarations of conformity	727247_EC OTi

	Documents and certificates	Document name	
PDF	Declarations of conformity	EU Declaration of Conformity 3667898	
PDF	Declarations of conformity	EATON(CEAG)-Conformity declaration AM00139_OTiDALl35_220_240_400_D_LT2_L	
PDF	Certificates	OTI DALI OT FIT D LT2 L CB DE1 58970 040320	
PDF	Certificates	VDE ENEC Certificate 40038085	
PDF	EU Data Act	Connected Products and Related Software and Services	
-			

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899494220	Unpacked 1	360 mm x 30 mm x 21 mm		0.23 dm ³
4052899494237	Shipping box 20	305 mm x 161 mm x 104 mm	4277.00 g	5.11 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.