

# PRODUCT DATASHEET DL IP44 FRAME DN 90 WT

DOWNLIGHT IP44 FRAME | Surface mounting frame for Downlight IP44



#### Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Shops
- Bathrooms

### Product benefits

- Easily installed

#### **Product features**


- Robust polycarbonate casing
- Mounting accessories included



## TECHNICAL DATA

# Dimensions & Weight

Diameter	90 mm
Height	47 mm
Product weight	50.00 g



#### Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

# Application & Mounting

Mounting type	Surface
Mounting location	Ceiling
Replaceable light source	No

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DL IP44 FRAME DN WT


	Documents and certificates	Document name	
POF	User instruction / safety instructions	DL IP44 FRAME DN BK/WT	
POF	Legal information	DL IP44 DN 115 8W 830 WT	
POF	Legal information	DL IP44 DN WT	
POF	Legal information	Informationstext 18 Abs 4 ElektroG	
POF	Declarations of conformity	DL IP44 FRAME DN	
POF	Declarations of conformity UKCA	UKCA Declaration of Conformity DOWNLIGHT IP44 DN WT	
	Tender texts	Document name	
	Tender documents	DOWNLIGHT IP44 FRAME DN 90 WT-EN	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075709881	Folding box 1	95 mm x 53 mm x 99 mm	74.00 g	0.50 dm <sup>3</sup>
4058075709898	Shipping box 10	279 mm x 200 mm x 115 mm	865.00 g	6.42 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### ADDITIONAL CATALOG INFORMATION



#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.