

PRODUCT DATASHEET

DL IP44 FRAME DN 165 WT

DOWNLIGHT IP44 FRAME | Surface mounting frame for Downlight IP44



Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Shops
- Bathrooms

Product benefits

- Easily installed

Product features


- Robust polycarbonate casing
- Mounting accessories included



TECHNICAL DATA

Dimensions & Weight

Diameter	165 mm
Height	47 mm
Product weight	96.00 g



DL IP44 FRAME DN 165



Materials & Colors







Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Mounting type	Surface
Mounting location	Ceiling

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	DL IP44 FRAME DN WT
 User instruction / safety instructions	DL IP44 FRAME DN BK/WT


Documents and certificates		Document name
	Legal information	DL IP44 DN 115 8W 830 WT
	Legal information	DL IP44 DN WT
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	DL IP44 FRAME DN
	Declarations of conformity UKCA	UKCA Declaration of Conformity DOWNLIGHT IP44 DN WT
Tender texts		Document name
	Tender documents	DOWNLIGHT IP44 FRAME DN 165 WT-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075709928	Folding box 1	170 mm x 53 mm x 174 mm	123.00 g	1.57 dm ³
4058075709935	Shipping box 10	350 mm x 279 mm x 190 mm	1495.00 g	18.55 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



Model	a [mm]	b [mm]	c [mm]	d [mm]	e [mm]	f [mm]	g [mm]	h [mm]
DL IP44 DN115	115	53	90	3-25	65	42	102	170
DL IP44 DN116	116	53	111	3-25	65	42	102	170
DL IP44 DN116	116	148	111	3-25	65	42	102	170
DL IP44 DN150	114	118	150	3-25	65	42	102	170
DL IP44 DN176	200	154	216	3-25	68	42	140	170

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.