

# PRODUCT DATASHEET TRUSYS FLEX P 35W 840 N CL WT EM

TruSys® FLEX EMERGENCY NARROW | Luminaire inserts with narrow light distribution for standard and emergency lighting, up to 175 lm/W



#### Areas of application

- Emergency illumination of escape routes
- Antipanic lighting
- Buildings requiring up to 3 h emergency light operation
- Direct replacement for luminaires with fluorescent lamps
- Industry halls, high rack warehouse, hardware stores

#### Product benefits

- Seamless integration of luminaires with emergency lighting function into general lighting
- Easy wiring thanks to included prewired driver and battery for Emergency lighting function
- Simple testing of luminaires with emergency lighting function thanks to integrated automatic test function
- Convenient visualization of results of automatic test with an included control LED
- Operation of integrated emergency lighting function with long life LiFePO4 battery with 3h battery discharge time
- High luminous efficacy in normal operation
- 3 years guarantee
- Directed light distribution for high heights
- Easy installation, no tools required for connection
- Energy saving and cost-effective
- Flexible application due to a range of different lumen packages and beam angles

#### **Product features**

- Certified according to European norms (EN 60598-1:2015; EN 60598-2-22:2014)



- Luminaire suitable for normal lighting and emergency lighting
- Self-contained luminaires
- Emergency lighting function: battery discharge time of 3 h
- Function test of emergency lighting: automatic (AT)
- Battery technology: LiFePO4
- Beam angle narrow: 60°
- Click into place solution with smart click buttons
- Fixed luminare taps
- Steel-sheet housing


## TECHNICAL DATA


#### Electrical data

Nominal wattage	35.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	160 mA
Inrush current	27.5 A
Inrush current time T <sub>h50</sub>	148 µs
Max. number of luminaires per miniature circuit breaker B16	22
Max. number of luminaires per miniature circuit breaker C10	17
Max. number of luminaires per miniature circuit breaker C16	27
Power factor $\lambda$	≥0.95
Total harmonic distortion	≤ 15 %
Protection class	I
Operating mode	Integrated LED driver

## Photometrical data

Luminous flux	6000 lm
Luminous efficacy	175 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Standard deviation of color matching	3 sdcm
Low flicker	Yes
Photobiological safety group acc. to EN62778	RG1
Beam angle	60 °






TRUSYS FLEX P 35W 840 N CL WT EM

TRUSYS FLEX P 35W 840 N CL WT EM

## Dimensions & Weight

Length	1500.00 mm
Width	77.70 mm
Height	39.40 mm
Product weight	2360.00 g



TRUSYS FLEX luminaire - clear

### Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9016
Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	0+40 °C
Temperature range at storage	-40+80 °C
Type of connection	Plug-In connection
Type of protection	IP40
Protection class IK (shock resistance)	IK04
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Mounting rail
Application environment	Indoor
Adjustable	No
With light source	Yes
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	100000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	76000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	89000 h
Lifespan L90/B10 at 25 °C	38000 h
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Control gear

Output current	430 mA
ECG - Output ripple current	< 5 %

#### **BATTERY**

Type of Battery	LiFePO4
Battery size [GMS]	Others
Nominal voltage of battery	3.2 V
Nominal capacity of battery	9000 mAh
Battery charging time	24 h

# **Emergency lighting**

Type of Emergency Lighting (EL)	EL unit (battery and controller) for decentral operation included	
Area of emergency application	Anti-panic lighting / Escape route lighting	
Type of emergency light operation	Non-maintained / Maintained	
Type of emergency operation test	Automatic	
Wattage in maintained operation mode	35.0 W	
Wattage in emergency operation mode	4 W	
Luminous flux in maintained operation mode	6000 lm	
Luminous flux in emergency operation mode	740 lm	
Battery life in emergency operation mode	3 h	

## Certificates & Standards

Standards	CE / CB / UKCA / ENEC / EAC
Luminaire with limited surface temperature, "D sign"	Yes
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

#### **EQUIPMENT / ACCESSORIES**

- Mounting rail with fixed integrated 8-pole cable

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	UI TRUSYS FLEX P EM
PDF	User instruction / safety instructions	TRUSYS FLEX EMERGENCY 840
POF	Legal information	Light Source Insert Trusys Flex EM


	Documents and certificates	Document name
POF	Legal information	Legal insert TRUSYS FLEX P EM
POF	Legal information	Informationstext 18 Abs 4 ElektroG
POF	Declarations of conformity	CE Declaration Trusys Flex P EM
POF	Declarations of conformity UKCA	UKCA Declaration Trusys Flex P EM
POF	Certificates	ENEC TRUSYS FLEX P EM
	Photometric and lighting design files	Document name
	IES file (IES)	TRUSYS FLEX P 35W 840 N CL WT EM
	LDT file (Eulumdat)	TRUSYS FLEX P 35W 840 N CL WT EM
	ULD file (DIALux)	TRUSYS FLEX P 35W 840 N CL WT
	ROLF file (RELUX)	TRUSYS FLEX P 35W 840 N CL WT
	UGR file (UGR table)	TRUSYS FLEX P 35W 840 N CL WT EM
	Light distribution curve type cone	TRUSYS FLEX P 35W 840 N CL WT EM
	Light distribution curve type polar	TRUSYS FLEX P 35W 840 N CL WT EM
	CAD/BIM files	Document name
	BIM Revit 3D	TRUSYS FLEX
	CAD STEP 3D	TruSys FLEX
	Tender texts Document	name
	Tender documents TruSys FLE	EX EMERGENCY NARROW 35W 840 N CL WT EM-EN
	UGR file (UGR table)  Light distribution curve type cone  Light distribution curve type polar  CAD/BIM files  BIM Revit 3D  CAD STEP 3D  Tender texts  Document	TRUSYS FLEX P 35W 840 N CL WT EM  TRUSYS FLEX P 35W 840 N CL WT EM  TRUSYS FLEX P 35W 840 N CL WT EM  Document name  TRUSYS FLEX  TruSys FLEX


LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075772915	Folding box	108 mm x 1,534 mm x 102 mm	2535.00 g	16.90 dm <sup>3</sup>
4058075772922	Shipping box 4	1,547 mm x 218 mm x 231 mm	10933.00 g	77.90 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.


#### ADDITIONAL CATALOG INFORMATION














#### References / Links

- For Guarantee see www.ledvance.com/guarantee

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.