

PRODUCT DATASHEET TRUSYS FLEX P RAIL 4500 5P WT

TruSys® FLEX ENERGY RAIL 5-POLE | 5-pole mounting rail



- Industry halls, high rack warehouse, hardware stores





Product benefits

- Simple installation
- High flexibility thanks to three available lengths (1500 mm, 3000 mm, 4500 mm and 1500 mm end rail)

Product features

- Through wired with 5 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	4650 mm
Width	70.2 mm
Height	38.8 mm
Product weight	4200.00 g



TRUSYS FLEX RAIL

Materials & Colors

Product color	White
Body material	Steel

Application & Mounting

	Mounting location	Ceiling
Ī	With light source	No
Ī	Replaceable light source	No

Certificates & Standards

Standards CE / CB / UKCA / ENEC / EAC

EQUIPMENT / ACCESSORIES

- Various accessories available

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instruction	ns TRUSYS FLEX P RAIL	
POF	Legal information	Informationstext 18 Abs 4 ElektroG	
POF	Declarations of conformity	CE Declaration of Conformity TRUSYS FLEX	
POF	Declarations of conformity UKCA	UKCA Declaration of Conformity TRUSYS FLEX	
POF	Declarations of conformity UKCA	TRUSYS FLEX	
	CAD/BIM files	Document name	
	BIM Revit 3D	TRUSYS FLEX	
	CAD STEP 3D	TruSys FLEX ER 4500	
	Tender texts	Document name	
	Tender documents	TruSys FLEX ENERGY RAIL 5-POLE 4500 5P WT-EN	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075793156	Sleeve 1	52 mm x 43 mm x 100 mm	4212.00 g	0.22 dm ³
4058075793163	Shipping box 4	4,729 mm x 191 mm x 141 mm	19895.00 g	127.36 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.