


PRODUCT DATASHEET OTi DALI 50/220...240/1A4 NFC L

OPTOTRONIC Intelligent - DALI NFC (SELV) | Constant Current - Indoor



Areas of application

- Linear lighting for office, education, industry, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for luminaires of protection class I

Product benefits

- Fully programmable via software (DALI Interface, NFC)
- Advanced luminaire/driver data (power, energy, operating hours...) for analytics
- DALI-2 certified incl. Parts 251, 252, 253
- Lifetime: up to 100,000 h (temperature at Tc = 65 °C, max. 10 % failure rate)
- High-quality dimming of 1...100 % by amplitude dimming
- $-\,$ Higher quality of light thanks to < 3 % output ripple current
- Very high efficiency
- Very low standby power consumption: < 0.15 W
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

Product features

- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Versatile DALI window driver up to 80 W due to flexible output characteristic
- Supply voltage: 220...240 V
- Available with output current range: up to 2,100 mA

- Constant Lumen Output (CLO)
- Integrated customizable thermal management (Driver Guard)

TECHNICAL DATA


Electrical data

Nominal wattage	54.00 W
Nominal output power	50 W
Nominal voltage	220240 V
Nominal output voltage	1554 V
Input voltage AC	198264 V
Input voltage DC	176276 V
U-OUT (working voltage)	60 V
Nominal output current	6001400 mA
Inrush current	≤ 20 A
Output current tolerance	±3 %
Output ripple current (100 Hz)	≤ 3 %
Mains frequency	0/50/60 Hz
Total harmonic distortion	≤ 10 %
Power factor λ	≥ 0.95
ECG efficiency	up to 91 %
Device power loss	5 W
Max. ECG no. on circuit breaker 10 A (B)	12
Max. ECG no. on circuit breaker 16 A (B)	20
Max. ECG no. on circuit breaker 25 A (B)	
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV
Operating frequency	0/50/60 Hz
Power loss in stand-by mode	≤0.15 W
Flickering metric (Pst LM)	≤1

Photometrical data

Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.4

Dimensions & Weight



Length	280.00 mm
Mounting hole spacing, length	270,0 mm
Width	30.00 mm
Height	21.00 mm
Cable cross-section, input side	0.51.5 mm ²
Cable cross-section, output side	0.51.5 mm ²
Wire preparation length, input side	8.09.0 mm
Wire preparation length, output side	8.09.0 mm
Product weight	209.00 g

Colors & materials

Casing material	Metal
Body material	Metal

Temperatures & operating conditions

Ambient temperature range	-25+60 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	100000 h		
Additional product data			
Encapsulated	No		
Capabilities			
Dimmable	Yes		

DALI

1...100 %

Dimming interface

Dimming range

Overheating protection	Yes
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	I
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

Certificates & Standards

Approval marks – approval	CE / VDE-ENEC / EAC / CCC / BIS / RCM	
Standards	Acc. to IEC 61347-1 / Acc. to IEC 61347-2-13 / Acc. to IEC 62384 / Acc. to IEC 62386 / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3 / Acc. to IEC 61347	
Protection class	T .	
Type of protection	IP20	
Energy efficiency class	A1	

LOGISTICAL DATA

Temperature range at storage	-40+85 °C
------------------------------	-----------

DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	OTI DALI NFC L
POF	Declarations of conformity	OTI DALI NFC L
POF	Declarations of conformity UKCA	OTI DALI NFC L
POF	Certificates	OTI DALI NFC L
POF	Certificates	OTI DALI NFC L
POF	Certificates	OTI DALI NFC L
POF	EU Data Act	Connected Products and Related Software and Services

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172074988	Unpacked 1	280 mm x 30 mm x 21 mm	209.00 g	0.18 dm ³
4062172074995	Shipping box 20	303 mm x 159 mm x 105 mm	4307.00 g	5.06 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.