

PRODUCT DATASHEET

Tracklight Rail 1M White

Tracklight rail and base | Tracklight rail and base

Areas of application

- Kitchens, living rooms, children's rooms or home offices
- Entrance areas



Product benefits

- Timeless elegant design
- Made of solid aluminum with high-quality appearance

Product features

- Customisable modular tracklight system



TECHNICAL DATA

Electrical data

| | |
|------------------|-------------|
| Nominal voltage | 220...240 V |
| Mains frequency | 50/60 Hz |
| Protection class | I |

Dimensions & Weight

| | |
|----------------|----------|
| Length | 1000 mm |
| Width | 35.0 mm |
| Height | 18.0 mm |
| Product weight | 460.00 g |



TRACKLIGHT RAIL 1M WT

Materials & Colors

| | |
|---------------|----------|
| Product color | White |
| Body material | Aluminum |

Application & Mounting

| | |
|---------------------------|-----------------|
| Ambient temperature range | -20...+40 °C |
| Type of connection | Terminal, 2-pin |
| Type of protection | IP20 |
| Mounting type | Surface |
| Mounting location | All surfaces |
| Replaceable light source | No |

Certificates & Standards

| | |
|----------------|-----------|
| Standards | CE / UKCA |
| Ball shot safe | No |




Accessories Optional

| Product image | Product name | EAN |
|---|-------------------------------------|---------------|
|  | Tracklight Flexible Connector White | 4058075764088 |
|  | Tracklight Linear Connector White | 4058075764002 |
|  | Tracklight Supply Connector White | 4058075763968 |
|  | Tracklight Cross Connector White | 4058075764125 |
|  | Tracklight Corner Connector White | 4058075764040 |
|  | Tracklight Suspension Kit White | 4058075764163 |

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|------------------------|
|  | User instruction / safety instructions | TRACKLIGHT RAIL |
|  | Declarations of conformity | TRACKLIGHT |
|  | Declarations of conformity UKCA | TRACKLIGHT ACCESSORIES |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075763920 | BAG 1 | 19 mm x 60 mm x 1,090 mm | 469.00 g | 1.24 dm ³ |
| 4058075763937 | Shipping box 16 | 1,027 mm x 227 mm x 115 mm | 8037.00 g | 26.81 dm ³ |
| 4099854116179 | Shipping box 4 | 1,010 mm x 82 mm x 56 mm | 2020.00 g | 4.64 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.