

# PRODUCT DATASHEET SMART+ Wifi Planon Frameless Sparkle 450x450mm TW

SMART+ Planon Frameless Sparkle | Panel frameless Sparkle effect luminaires with WiFi technology



#### Areas of application

- Kitchens, living rooms, children's rooms or home offices
- Entrance areas

## **Product benefits**

- Creating individual light scenes according to your needs with cold white to warm white (3000 K to 6500 K)
- Elegant design
- Frameless panel luminaire
- Sparkle effect that creates a sky night effect
- Easy and quick installation

#### **Product features**

- Ceiling luminaire with advanced LED technology
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Sparkle effect



September 15, 2025, 04:42:25 SMART+ Wifi Planon Frameless Sparkle 450x450mm TW

## **TECHNICAL DATA**

# Electrical data

| Nominal wattage   | 24.50 W    |
|---|------------|
| Nominal voltage   | 220240 V   |
| Mains frequency   | 5060 Hz    |
| Nominal current   | 135.000 mA |
| Inrush current time T <sub>h50</sub>                        | 1900 µs    |
| Max. number of luminaires per miniature circuit breaker B16 | 29         |
| Max. number of luminaires per miniature circuit breaker C16 | 49         |
| Power factor $\lambda$                                      | ≥0.7       |
| Total harmonic distortion                                   | < 20 %     |
| Protection class  | I          |


# Photometrical data

| Luminous flux  | 1300 lm              |
|--|----------------------|
| Total luminous flux of contained light sources               | 2250 lm              |
| Luminous efficacy  | 53 lm/W              |
| Color temperature  | 30006500 K           |
| Reference control setting of contained light source (Kelvin) | 3000 K <sup>1)</sup> |
| Light color (designation)                                    | Tunable White        |
| Color rendering index Ra                                     | > 80                 |
| Standard deviation of color matching                         | ≤6 sdcm              |
| Flickering metric (Pst LM)                                   |                      |
| Stroboscope effect metric (SVM)                              |                      |
| Photobiological safety group acc. to EN62778                 | RG1                  |

1) Performing a reset will restore the default values set by the manufacturer

# **Dimensions & Weight**

| Length         | 450.00 mm |
|----------------|-----------|
| Width          | 450.00 mm |
| Height         | 63.00 mm  |
| Product weight | 1860.00 g |



# Materials & Colors

| Product color                              | White  |
|--|--------|
| Housing color                              | White  |
| Body material                              | Steel  |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content                            | 0.0 mg |

# Application & Mounting

| Ambient temperature range | -20+40 °C                   |  |
|---------------------------|-----------------------------|--|
| Type of connection        | Terminal, 3-Pole (L, N, PE) |  |
| Type of protection        | IP20                        |  |
| Dimmable                  | Yes                         |  |
| Type of dimming           | WiFi                        |  |
| Mounting type             | Surface                     |  |
| Application environment   | Indoor                      |  |
| With light source         | Yes                         |  |

# Lifespan

| Lifespan L70/B50 at 25 °C  | 30000 h |
|----------------------------|---------|
| Number of switching cycles | 15000   |

# **Certificates & Standards**

| Standards  | CE / UKCA       |  |
|--|-----------------|--|
| Luminaire with limited surface temperature, "D sign" | No              |  |
| Ball shot safe                                       | No              |  |
| Replaceable light source (EPREL)                     | Not replaceable |  |

#### Additional product data

| Product remark        | Reset settings to default by switching the product on for three seconds<br>and off for three seconds and repeating this five times. |  |
|-----------------------|---|--|
| Number of illuminants | empty   |  |

## EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

- Complete mounting and connecting accessories included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

## DOWNLOAD DATA

|     | Documents and certificates  | ertificates Document name       |  |
|-----|---|---------------------------------|--|
| PDF | User instruction / safety instructions UI_SMART WIFI PLANONFL SPARK |                                 |  |
| POF | Extended installation guide   | SMART+ WIFI INSTALLATION GUIDE  |  |
| POF | Declarations of conformity  | SMART WIFI                      |  |
| POF | EU Data Act   | SMART WiFi Lamps and Luminaires |  |

# LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075759541 | Folding box<br>1             | 82 mm x 502 mm x 503 mm              | 2473.00 g    | 20.71 dm <sup>3</sup> |
| 4058075759558 | Shipping box<br>4            | 525 mm x 347 mm x 528 mm             | 10903.00 g   | 96.19 dm³             |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **References / Links**

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.