

PRODUCT DATASHEET ENDURA Classic Cube Adjustable Wall Black

Endura Classic Cube ADJ Wall | Outdoor Endura Classic Cube with socket GU10



Areas of application

- Entrance lighting
- Patios, balconies
- Building facades

Product benefits

- High flexibility in the choice of the light source thanks to GU10 socket
- Easy and quick installation
- High-quality materials

Product features

- Die-cast aluminum housing
- Adjustable luminaire head



TECHNICAL DATA

Electrical data

| Nominal voltage | 220240 V |
|------------------|----------|
| Mains frequency | 5060 Hz |
| Protection class | |

Photometrical data

| Flickering metric (Pst LM) | - |
|---------------------------------|---|
| Stroboscope effect metric (SVM) | - |

Dimensions & Weight

| Length | 66.00 mm |
|----------------|-----------|
| Width | 93.00 mm |
| Height | 100.00 mm |
| Product weight | 500.00 g |



Materials & Colors

| Product color | Black |
|-----------------|----------|
| Housing color | Black |
| Body material | Aluminum |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|--|-----------------------------|
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP44 |
| Protection class IK (shock resistance) | IK04 |
| Dimmable | No |
| Mounting type | Surface |

| Application environment | Outdoor |
|--------------------------|---------|
| Adjustable | Yes |
| With light source | No |
| Replaceable light source | No |
| Holder designation | GU10 |

Certificates & Standards

| Standards | CE / UKCA | |
|--|-----------|--|
| Luminaire with limited surface temperature, "D sign" | No | |
| Ball shot safe | No | |

Additional product data

| Product remark | Maximum bulb wattage: 35 W |
|-----------------------|----------------------------|
| Number of illuminants | 1 |

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|--|------------------------------|
| PDF | User instruction / safety instructions | ENDURA CLASSIC CUBE ADJ WALL |
| PDF | Legal information | Legal insert I-Outdoor |
| PDF | Declarations of conformity | ENDURA CLASSIC |
| PDF | Declarations of conformity UKCA | Fixed LUM without EMC |
| - | | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075763562 | Folding box 1 | 82 mm x 112 mm x 122 mm | 566.00 g | 1.12 dm ³ |
| 4058075763579 | Shipping box 6 | 263 mm x 130 mm x 272 mm | 3635.00 g | 9.30 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.